



Item no.: 736-203
 Product description: DOUBLE DECK PCB TERMINAL STRIP 2 SOLDER PINS STRAGGERED BY HALF THE PIN SPACING 3X2 POLE PIN SPACING 5 MM / 0.197 IN



Produkt kann von Bild abweichen / product may differ

Packing unit 112 pieces

RoHS compliant

Product group	4 (Printed Circuit)
Weight	7.14 g
Color	gray
No. of connection Points	6
No. of potentials	6
pole count	3
Height	26.5 mm
Height	1.04 in
Width	16 mm
Width	0.63 in
Depth	21 mm
Depth	0.827 in
Pin spacing from	5 mm
Pin spacing from	0.197 in
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	4 kV
Current intensity EN	21 A

Pollution degree	2
Measured voltage EN	630 V
Measured shock voltage	4 kV
Current intensity EN	21 A



Connection method	CAGE CLAMP® CONNECTION
Cross section [mm ²]	0.08 - 2.5 mm ²
Wiring method	solid
Cross section [mm ²]	0.08 - 2.5 mm ²
Cross section [mm ²]	0.25 - 1.5 mm ²
Cross section [mm ²]	0.25 - 2.5 mm ²
Cross section [AWG]	28 - 12 AWG
Strip length from	5 mm
Strip length to	6 mm
Material group	I



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
736-203	ABS	04-HG469925/1-PDA	250	12	0,5-2,5
736-203	BV	11915/A0	250	12	0,5-2,5
736-203	CCA	NL6266	250	12	0,5-2,5
736-203	CSA	18677-26	300	10	28-12
736-203	DNV	E-9215	250	12	0,5-2,5
736-203	GL	17296-00HH	250	12	0,5-2,5
736-203	KEMA	2110204.06	250	12	0,5-2,5
736-203	RMR	11130002	250	12	0,5-2,5
736-203	UR	E45172	300	10	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected