


Item no.: 770-2115/007-000
 Product description: PLUG SNAP IN TYPE 5 POLE 100% PROTECTED AGAINST MISMATING WITH DIRECT CONTACT OF THE GROUND CONDUCTOR



Produkt kann von Bild abweichen / product may differ

Packing unit 100 pieces

RoHS compliant

| | |
|----------------------------------|-------------------------|
| Product group | 20 (WINSTA) |
| pole count | 5 |
| Cross section [mm ²] | 0.5 - 4 mm ² |
| Cross section [AWG] | 20 - 12 AWG |
| Connection method | CAGE CLAMP®S Connection |
| Number of strands | 2 |
| Measured voltage EN | 400 V |
| Measured shock voltage | 6 kV |
| Pollution degree | 3 |
| Current intensity EN | 25 A |
| Weight | 20.48 g |
| Color | blue |
| No. of connection Points | 10 |
| No. of potentials | 5 |
| Height | 18.5 mm |
| Height | 0.728 in |
| Width | 55.5 mm |
| Width | 2.185 in |

| | |
|-------------------|----------|
| Depth | 36 mm |
| Depth | 1.417 in |
| Strip length from | 9 mm |
| Strip length to | 9 mm |
| Strip length | 0.35 in |



| Item no. | Admission office | Approval no. | Voltage [V] | Current [A] | Cross section [mm ²] |
|------------------|------------------|---------------------|-------------|-------------|-----------------------------------|
| 770-2115/007-000 | ABS | 06-HG154986/11-PDA | 400 | 25 | 0,5-4,0 |
| 770-2115/007-000 | CCA | | 400 | 25 | 0,5-4,0 |
| 770-2115/007-000 | cURus | E45171 | 600 | 20 | 12 |
| 770-2115/007-000 | KEMA | | 400 | 25 | 0,5-4,0 |
| 770-2115/007-000 | PRS | TE/1719/880590/08 | 400 | 25 | 0,5-4,0 |
| 770-2115/007-000 | PSE | Jet 0695-43009-1002 | 600 | 20 | 12 |

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected