



E3AS-F1500IMT 2M

Photoelectric sensor, rectangular housing, stainless steel, infrared laser class 1, time-of-flight, 1500 mm, PNP, Light-ON/Dark-ON, IO-Link COM3, 2 m cable

Specifications

Shape	Cuboid
Sensing method	Background suppression
Sensing distance	1500 mm
Sensing distance (min.)	50 mm
Setting method	IO-Link, Teach-In
Connection method	Cable
Cable length	2 m
Output type	IO-Link, PNP
Operation mode	Dark-ON, Light-ON
IO-Link baud rate	COM3 (230.4 kbps)
Response time	150 ms
Material housing	Stainless steel
Product Width (unpacked)	11.4 mm
Product Height (unpacked)	38 mm
Product Depth (unpacked)	22 mm
Type of light	Laser diode, infrared light
Laser class	1
Spot size	95 mm
Power supply voltage	10-30 V
Features	TOF (Time of Flight)

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 12 February, 2024. Click here for [terms of use](#).

Accessories



E39-L201

Mounting bracket for E3AS sensor, L shaped



E39-L202

Protective mounting bracket for E3AS, vertical mounting



E39-L203

Mounting bracket for E3AS sensor, rear mounting



E39-L204

Protective metal cover for E3AS, horizontal surface mounting

Downloads

CAD Library



**E3AS – Automotive
Brochure**

EN PDF 18.7 MB



**E3AS – Food &
Commodities
Datasheet**

EN PDF 18.1 MB



**E3AS-F
Index list**

EN PDF 235 KB



**E3AS-F
Instruction Sheet**

EN PDF 1.38 MB



**E3AS-Fxxxxxx
IO-Link IODD file**

EN ZIP 1.1 MB



**EAC Mark removal
Discontinuation Notice**

EN PDF 221 KB



**IO-Link Series
Brochure**

EN PDF 8.05 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 12 February, 2024. Click here for [terms of use](#).