

## Han F+B CA 17D 0,5mm<sup>2</sup> f/- st/- PUR 7,5m



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                     |
|--------------------|-------------------------------------------------------------------------------------|
| Part number        | 33 50 420 0306 075                                                                  |
| Specification      | Han F+B CA 17D 0,5mm <sup>2</sup> f/- st/- PUR 7,5m                                 |
| HARTING eCatalogue | <a href="https://harting.com/33504200306075">https://harting.com/33504200306075</a> |

### Identification

|               |                           |
|---------------|---------------------------|
| Category      | System cabling            |
| Series        | Han® F+B                  |
| Element       | Cable assemblies          |
| Specification | Pre-assembled on one side |
| Connector 1   | Female<br>Hood            |
| Type of cable | Copper cable (round)      |

### Version

|                    |                     |
|--------------------|---------------------|
| Cable length       | 7.5 m               |
| Number of cores    | 17                  |
| Core structure     | 0.5 mm <sup>2</sup> |
| Number of contacts | 17                  |
| PE contact         | Yes                 |

### Technical characteristics

|                                        |                                                |
|----------------------------------------|------------------------------------------------|
| Rated current                          | 10 A                                           |
| Rated voltage                          | 400 V                                          |
| Rated impulse voltage                  | 6 kV                                           |
| Pollution degree                       | 3                                              |
| Limiting temperature                   | -20 ... +80 °C moved<br>-40 ... +80 °C unmoved |
| Degree of protection acc. to IEC 60529 | IP69                                           |



Pushing Performance  
Since 1945

Technical characteristics

|                        |                                       |
|------------------------|---------------------------------------|
| Minimum bending radius | 10x Cable diameter (repeated bending) |
|                        | 5x Cable diameter (singular bending)  |

Material properties

|                  |                    |
|------------------|--------------------|
| Material (cable) | PUR (polyurethane) |
| Colour (cable)   | Grey               |

Specifications and approvals

|                |                       |
|----------------|-----------------------|
| Specifications | EN 50525-1            |
|                | IEC 60228             |
|                | EN 50363-3            |
|                | EN 50363-10-2         |
| Approvals      | Ecolab Topactive 200  |
|                | Ecolab Topactive 500  |
|                | Ecolab Topactive OKTO |
|                | Ecolab Topax 66       |
|                | Ecolab Topax 990      |

Commercial data

|                                |                                         |
|--------------------------------|-----------------------------------------|
| Packaging size                 | 1                                       |
| Country of origin              | Germany                                 |
| European customs tariff number | 85444290                                |
| GTIN                           | 5713140238213                           |
| eCl@ss                         | 27060311 Assembled sensor actuator-line |
| ETIM                           | EC001855                                |
| UNSPSC 24.0                    | 26121604                                |