

Conductor marker carrier - PATG 3/23 - 1013863

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Conductor marker carrier, transparent, unlabeled, mounting type: slide on, cable diameter range: 4-7 mm, lettering field size: 23 x 4 mm

Why buy this product

- The corresponding UC-WMT ..., US-WMT ..., UCT-WMT ... and EMT ... insert labels are used for marking
- The PATG ... collar is a captive marker carrier
- These conductor marking systems consist of marker carriers and insert labels
- Can be used to mark conductors with a diameter of 0.6 ... 50 mm

Key Commercial Data

Packing unit	1 STK
Minimum order quantity	500 STK
GTIN	 4 017918 014056
GTIN	4017918014056
Weight per Piece (excluding packing)	0.782 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

Dimensions

Length (b)	23 mm
Width (a)	7.5 mm
Cable diameter	4 mm ... 7 mm

Ambient conditions

Conductor marker carrier - PATG 3/23 - 1013863

Technical data

Ambient conditions

Ambient temperature (operation)	-50 °C ... 80 °C
---------------------------------	------------------

General

Color	transparent
Type	Profile
Components	Silicone-free
Flammability rating according to UL 94	V0
Material	PVC
RoHS compliant	Yes
Test for substances that would hinder coating with paint or varnish	VW PV 3.10.7:2005-02
Result	Test passed
Marking mounting type	slide on

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

REACH SVHC	DOTC 15571-58-1
------------	-----------------