

Data sheet Product LA ICK PEN 16 W 12 A




Heatsinks and active heatsinks for processors>Active heatsinks for processors
for Intel Pentium and MMX

Features

way of fixation:	therm. cond. adhesive
socket:	• socket 7 • socket 370
thermal resistance:	1.2 K/W
suitable for processor type:	• AMD® K6-III • IDT W2A • Cyrix MII and similar • MMX • IDT C6 • Intel® Pentium® • AMD® K6-2
dissipation loss:	51.1 W
operating voltage of the fan motor:	12 V
surface:	black anodised
accessories:	alarm exit

Technical Drawing



A: 50.8 mm

B: 50.8 mm

C:	16.51 mm
D:	26.51 mm

Fan

circuit voltage:	12 V DC
bearing type:	double ball bearing
fan dimensions:	40x40x10 mm
cur. consumpt.:	50 mA
max. iuitial current:	130 mA
max. volume flow:	173 l/min 10,4 m³/h
max. static pressure:	2.9 mmH₂O 28.5 Pa
noise level:	25 dB(A), 1 m frontal
temperature range:	-40°C... +85°C
failure rate (L ₁₀):	40.000 h (40°C)
MTBF:	350.000 h (40°C)
weight:	13 g
cases:	plastic PBT (UL E54695)