

InduCom 25p special for PCB K screw



Image is for illustration purposes only. Please refer to product description.

Part number	61 03 001 0317
Specification	InduCom 25p special for PCB K screw
HARTING eCatalogue	https://harting.com/61030010317

Identification

Category	Hoods / Housings
Series	D-Sub
Identification	InduCom
Type of hood/housing	Shell housing
Description of hood/housing	Suitable for circuit boards

Version

Size	D-Sub 3
Version	Top entry
Number of cable entries	1
Cable entry	1x
Strain relief	In case of strain relief for one cable, DIN 41612 insert or cable clamps must be used. In case of strain relief for one or two cables, D-Sub insert and cable clamp or crimp flange and crimp ferrule combination must be used.
Locking type	Knurled screw Thread 4-40 UNC
ground connection	Without internal grounding block
2 parts	Yes
Separable	Yes
Pack contents	Fixing screws

Technical characteristics

Tightening torque	0.4 Nm Fixing screws 0.4 Nm cover screw 0.4 Nm Locking screw
-------------------	--



Pushing Performance
Since 1945

Technical characteristics

Limiting temperature -55 ... +125 °C

Degree of protection acc. to IEC 60529 IP30

Material properties

Material (hood/housing) Zinc die-cast

Material (screw) Steel, nickel plated

Length 60.7 mm

Width 51.7 mm

Height 25 mm

RoHS compliant

ELV status compliant

China RoHS e

REACH Annex XVII substances Not contained

REACH ANNEX XIV substances Not contained

REACH SVHC substances Not contained

California Proposition 65 substances Not contained

Commercial data

Packaging size 10

Net weight 93.74 g

Country of origin China

European customs tariff number 85389099

GTIN 5713140222618

eCl@ss 27440213 D-Sub hood

ETIM EC001133

UNSPSC 24.0 39121416