

MU4 technical data



Photo of example product

Part number	MU400X6P
Product Description	MU4FSDL 15SBSG 15SBSG 5SBSG B/S
Input voltage range	85 - 264VAC (Single phase)
3 Outputs	1. 15V @ 20A (20A max) 6.00V to 15V, 240W max. 2. 15V @ 20A (20A max) 6.00V to 15V, 240W max. 3. 5V @ 30A (30A max) 3.30V to 6V, 150W max.
Total output power	Low line = 600W, high line = 800W
Earth leakage	300 µA
Cooling	Variable speed forward air fan
Operating temperature	-20.0°C - 70.0°C (Minimum startup temperature -40.0°C)
Max operating altitude	5000.0m
Case or mounting option	Enclosed
Unit signals and controls	Controls: module inhibit, remote sense Signals: DC good

Isolation	Input to earth	Input to output	Output to earth
	1.5kVac / 1 x MOPP	4.0kVac / 2 x MOPP	1.5kVac / 1 x MOPP
Input connection	Screw		
Input fuses	All supply lines fused		
Dimensions (mm)	254 x 89 x 41mm (10 x 3.5 x 1.61in)		
Weight	880g		
Approvals	CE, EN/IEC/UL60601-1, EN/IEC/UL60950-1, EN/IEC/UL62368-1, UKCA		
Features and benefits	• Very low audible noise. • Designed for BF medical applications. • Meets EN55032 Class B EMC. • Individual output adjustment. • PMBus option. • Fits 1U applications.		
Warranty	7 Years		
Datasheet			