

M12 A-cod 5-pol st /- m /- PUR 0.30m



Image is for illustration purposes only. Please refer to product description.

Part number	C2 13 200 0000 0359
Specification	M12 A-cod 5-pol st /- m /- PUR 0.30m
HARTING eCatalogue	https://harting.com/C21320000000359

Identification

Category	System cabling
Series	Circular connectors M12
Element	Cable assemblies
Specification	Pre-assembled on one side
Connector 1	M12 A-coding
	Male Straight
	Overmoulded
Type of cable	Copper cable (round)
Description of the cable	Halogen-free

Version

Cable length	0.3 m
Number of cores	5
Core structure	5x 0.34 mm ²
Termination method	Crimp termination
Shielding	Unshielded
Coding	A-coding

Technical characteristics

Rated current	4 A
Rated voltage	60 V
Limiting temperature	-25 ... +80 °C moved
	-40 ... +80 °C unmoved
Degree of protection acc. to IEC 60529	IP65 / IP67 mated condition



Pushing Performance
Since 1945

Technical characteristics

Cable diameter	4.5 mm
Minimum bending radius	10x Cable diameter (repeated bending) 5x Cable diameter (singular bending)

Material properties

Material (cable)	PUR (polyurethane)
Colour (cable)	RAL 7021 (black grey)
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

Specifications and approvals

Specifications	IEC 61076-2-101 UL 1581 IEC 60332-2-2 Flame retardancy
UL / CSA	UL in preparation
Approvals	CE

Commercial data

Packaging size	4
Country of origin	Romania
European customs tariff number	85444290
GTIN	5713141002844
eCl@ss	27060311 Assembled sensor actuator-line
ETIM	EC001855