

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Portable hand-held device, battery-powered, for processing 1.5 mm² taped ferrules with function end, suitable for PVC insulated conductors (H07V-K), incl. battery, charger, CUTFOX 12 cable cutter, service tool for troubleshooting, and one 1.5 mm² strip of ferrules, packed in a robust case.

## Your advantages

- The product innovation for switchgear manufacturing the CRIMPHANDY. You can strip and crimp your conductors in under two seconds using this portable hand-held machine. This step takes 75% less time than before.
- Consistently optimum results thanks to automatic monitoring functions
- Unlimited mobile use thanks to battery operation and magazine



## **Key Commercial Data**

Packing unit	1 pc
GTIN	4 046356 589154
GTIN	4046356589154
Weight per Piece (excluding packing)	1,463.000 g
Custom tariff number	84672920
Country of origin	Germany

### Technical data

### Dimensions

Length (b)	205 mm
Width (a)	43 mm
Height (c)	70 mm
Conductor diameter area (GRP)	2.4 mm 3.1 mm
Stripping length	10.8 mm

#### General

Color	black
Compression	Square crimp
Type of contact	Ferrules



## Technical data

### General

Power consumption	20 W
Conductor type	PVC H07V-K
Maximum stripping length	10.8 mm
Insertion length minimum	32 mm
Min. cross section	1.5 mm <sup>2</sup>
Max. cross section	1.5 mm²
Weight	0.43 kg

## **Environmental Product Compliance**

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 25;
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

## Classifications

## eCl@ss

eCl@ss 10.0.1	17130101
eCl@ss 11.0	17130101
eCl@ss 4.0	21040300
eCl@ss 4.1	21040300
eCl@ss 5.0	21040300
eCl@ss 5.1	17130100
eCl@ss 6.0	17130100
eCl@ss 7.0	17130101
eCl@ss 8.0	17130101
eCl@ss 9.0	17130101

### **ETIM**

ETIM 4.0	EC000163
ETIM 5.0	EC002778
ETIM 6.0	EC002778
ETIM 7.0	EC002778

### **UNSPSC**

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518
UNSPSC 18.0	27111518
UNSPSC 19.0	27111518



## Classifications

### **UNSPSC**

UNSPSC 20.0	27111518
UNSPSC 21.0	27111518

## Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC [H[

RU C-DE.Al30.B.01549

#### Accessories

Accessories

Assembly tool

Tool - CF CRIMPHANDY 1,5/SERVICE-TOOL - 1212708



Service tool, for CF-CRIMPHANDY 1,5, for rectifying malfunctions

Replacement part - CF CRIMPHANDY 1,5/GP2 - 1212844



Waste guide plate 2, for CF CRIMPHANDY 1,5



### Accessories

Replacement part - CF CRIMPHANDY/GP1 - 1212514



Waste guide plate 1, for CF CRIMPHANDY 0,5 /0,75 /1,0/1,5

### Battery module

Battery - CF CRIMPHANDY/ACCU - 1212518



Replacement battery for CRIMPHANDY..., Li-ion 7.4 V, 0.68 Ah

#### Cable end sleeve

Ferrule - AI 1,5-8 BK-S - 1212524



Band ferrules, 1.5 mm², sleeve length 8 mm, with plastic collar, according to DIN 46228-4, color: black, equipped with function end for safe and convenient processing with the Crimphandy, 20 strips with 50 sleeves per strip.

#### Ferrule - AI 1.5-8 RD-S - 1212781



Taped ferrules, 1.5 mm², sleeve length: 8 mm, with plastic collars, according to DIN 46228-4, special color: red, with function end for safe and convenient processing with the Crimphandy, 20 strips each with 50 sleeves per strip.

### Charger

Charger - CF CRIMPHANDY/CHARGER - 1212519



Replacement charger, for 100 V  $\dots$  240 V AC mains voltage, short charging time, short-circuit-proof, protected against polarity reversal, operating state indicator

Cover



### Accessories

Cover - CF CRIMPHANDY/COVER - 1212709



Replacement receptacle tray for CF-CRIMPHANDY

Cutting tool - CF CRIMPHANDY CUTTER - 1212520



Cutting unit, for CF CRIMPHANDY, for stranded copper wires from 0.5 - 1.5 mm², incl. receptacle tray

Phoenix Contact 2020 @ - all rights reserved http://www.phoenixcontact.com