	1			2	3		4	5	
	-7.13	-10.28 REF 2.70	±0.20 + 6.95±0.20 + 6.95±0.20 + 6.95±0.20 + 6.95±0.20 +	15.80±0.25	2.50 0.92±0.08 0.92±0.08 1.2.3 0.07±0.08 1.3.14±0.12 RECOMMENDED PCB THICKN RECOMMENDED PCB THICKN	<u>2.50</u> <u>\$2.30±0.08</u>	TECHNICAL CHARACTE MATERIAL INSULATOR: PBT FLAMMABILITY RATING COLOR: WHITE CONTACT MATERIAL: C CONTACT TYPE: STAMI CONTACT PLATING: SE SHIELDING: BRASS NI I QUALITY CLASS: 1500 I ENVIRONMENTAL OPERATING TEMPERAT COMPLIANCE: LEAD FF ELECTRICAL CURRENT RATING: 1.5 WORKING VOLTAGE: 30 INSULATOR RESISTANC	RISTICS : UL94-V0 OPPER ALLOY PED LECTIVE GOLD PLATED MATING CYCLES 	
Ro N	HS Compliant 09-AVR-15	PCB THIKNESS	QP	PROJECTION:	GENERAL TOLERANCE		-~		
M	27-OCT-14	REVIEW	QL	-	$X = ^{+}/_{0.2}$				
L	29-AUG-13	AXEL MAKE UP	QL				ř		F
ĸ	24-JUL-13	DRAWING	QL		.XX = ⁺ /_ 0.15	WÜRTH ELEKTRO	NIK		
K J		DESIGNATION			UNIT: MM		2.0 FEMALE R/A A TYPE		SIZE
J	15-FEV-13		AR	APPROVAL: NPr		DESCRIPTION: USB	2.0 FEWIALE R/A A I YPE		SIZE
	08-NOV-11	CURRENT RATING			SCALE:				
н	03-OCT-11	UL	GG		SHEET: 1/3	WERI PART NO: 614	004 160 21		A4

1	2	3	4	5	\Box
	130±1.0	300±1.0	Note: 1.Dimension: Tray Size: 300(L)X13 Carton Size:322X28 2.Quqntity: 60pcs/Tray 44Tray/ Carton Q'TY: 2640pcs 3.G.W: 7.12KG/Carto	5X350 (mm)	A
ł	 Two Row				в
TRAY			→ CARTON	350	С
G	APPROVAL: NPr	GENERAL TOLERANCE .X = +/_ 0.2 .XX = +/_ 0.15 UNIT: MM	WÜRTH ELEKTRONIK		
B A REV DATE FILE	BY AFFROVAL NFI	SCALE: SHEET: 2/3 DRAW: QL	WERI PART NO: 614 004 160 21		D

1	2	3	4	5	-
					_

А

В

С

Cautions and Warnings:

This electronic component is designed and developed with the intention for use

in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

R	toHS Compliant							
G				PROJECTION:	GENERAL TOLERANCE			1
F					.X = ⁺ /_ 0.2			
E					.XX = ⁺ /_ 0.15			
D						WÜRTH ELEKTRONĬK		
С				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE	Ъ
В					SCALE:			Р
A	10-SEP-14	PDF	QL		SHEET: 3/3	WERI PART NO: DISCLAIMER	A4	
REV	DATE	FILE	BY		DRAW: QL			