



PYFZ-08-E

Socket, DIN rail/surface mounting, 8-pin, screw terminals (standard)

Specifications

Applicable product family	G3F, H3YN, MY2, MY2-GS
Mounting method	DIN rail/screw
Terminal	Screw
Product Width (unpacked)	23 mm
Product Height (unpacked)	31 mm
Product Depth (unpacked)	72 mm
Color	Black
Hold down clip included	×
Release Lever included	×
Applicable ferrules	Forked terminals

Fits to



MY2-GS-R AC110/120

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 110/120 VAC



MY2-GS-R AC12

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 12 VAC



MY2-GS-R AC220/240

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 220/240 VAC



MY2-GS-R AC24

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 24 VAC

**MY2-GS-R AC48**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 48 VAC

**MY2-GS-R DC100/110**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 100/110 VDC

**MY2-GS-R DC12**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 12 VDC

**MY2-GS-R DC24**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 24 VDC

**MY2-GS-R DC48**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 48 VDC

**MY2IN-CR-GS-R AC110/120**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button. 110/120 VAC

**MY2IN-CR-GS-R AC220/240**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button. 220/240 VAC

**MY2IN-D2-GS-R DC100/110**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button. 100/110 VDC

**MY2IN-D2-GS-R DC12**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button, 12 VDC

**MY2IN-D2-GS-R DC24**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button, 24 VDC

**MY2IN-GS-R AC110/120**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 110/120 VAC

**MY2IN-GS-R AC12**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 12 VAC

**MY2IN-GS-R AC220/240**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 220/240 VAC

**MY2IN-GS-R AC24**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 24 VAC

**MY2IN-GS-R AC48**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 48 VAC

**MY2IN-GS-R DC100/110**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 100/110 VDC

**MY2IN-GS-R DC12**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 12 VDC

**MY2IN-GS-R DC24**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 24 VDC

**MY2IN-GS-R DC48**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 48 VDC

**MY2IN1 12VDC (S)**

Relay, plug-in, 8-pin, DPDT, reverse coil polarity, 10 A, mech & LED indicators, lockable push to test button, label facility

**MY2K-02 24VDC**

Latching relay, pcb pins, 14-pin, DPDT, 3 A, LED indicator, 24 VDC

**MY2N1 12VDC (S)**

Relay, plug-in, DPDT, reverse coil polarity, 10 A, mech. & LED indicator, 12 VDC

**MY2N1 24VDC (S)**

Relay, plug-in, DPDT, reverse coil polarity, 10 A, mech. & LED indicator, 24 VDC

**MY2N1-D2 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, reverse coil polarity, 10 A, mech & LED indicators, coil suppressor, label facility, 24 VDC

**MY2Z 24VDC**

Relay, plug-in, DPDT (bifurcated), 3 A, mechanical indicator, 24 VDC

**MY2ZN 220/240VAC**

Relay, plug-in, DPDT (bifurcated), 3 A, mech. & LED indicator, 220/240 VAC

**MY2ZN 24VDC**







Relay, plug-in, 8-pin, DPDT, bifurcated contacts, 10 A, mech & LED indicators, label facility, 24 VDC

**MY2ZN-D2 24VDC**

Relay, plug-in, 8-pin, DPDT, bifurcated contacts, 10 A, mech & LED indicators, coil suppressor, label facility, 24 VDC

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 14 February, 2024. Click here for [terms of use](#).

	PFP-100N	DIN-rail mounting track, 35 x 7.3 mm, 1 m length
	PFP-100N2	DIN-rail mounting track, 35x16mm, 1m length
	PFP-50N	Din rail track, 500 mm
	PFP-M	End plate
	PFP-S	Spacer
	PYC-A1	Retaining clips for LY/MY relay & PTF/PYF_E/N socket
	PYC-E1	Retaining clips for MY2IN(S) relay & PYF_A/N socket
	XW5Z-EP12	Separator Plate for terminal blocks, 12 mm width
	XW5Z-EP6	End bracket for terminal blocks, 6 mm width
	Y92H-3	Clips for H3Y(N) timer & PYF socket

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



MY(S) Miniature Power Relays Datasheet

EN PDF 9.29 MB