


Item no.: 218-510
 Product description: 1-CONDUCTOR PCB TERMINAL STRIP 10 POLE 2 SOLDER PINS / WITH LOCKING SIDE PIN SPACING 2.54 MM / 0.1 IN



Produkt kann von Bild abweichen / product may differ

Packing unit 160 4*40 pieces

RoHS compliant

Product group	4 (Printed Circuit)
Weight	3.312 g
Color	gray
No. of connection Points	10
No. of potentials	10
pole count	10
Height	8.1 mm
Height	0.319 in
Width	26.9 mm
Width	1.059 in
Depth	13 mm
Depth	0.512 in
Pin spacing from	2.54 mm
Pin spacing from	0.1 in
Pollution degree	2
Measured voltage EN	160 V
Measured shock voltage	2.5 kV
Current intensity EN	6 A
Pollution degree	2

Measured voltage EN	320 V
Measured shock voltage	2.5 kV
Current intensity EN	6 A



Connection method	CAGE CLAMP® CONNECTION
Cross section [mm ²]	0.08 - 0.5 mm ²
Wiring method	solid
Cross section [mm ²]	0.08 - 0.5 mm ²
Cross section to [mm ²]	0.25 mm ²
Cross section to [mm ²]	0.25 mm ²
Cross section [AWG]	28 - 20 AWG
Strip length from	5 mm
Strip length to	6 mm
Material group	I
xxx-xxx/000-005	red
xxx-xxx/000-006	blue
xxx-xxx/000-012	orange
xxx-xxx/000-023	green



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
218-510	CCA	NL5749	250	6	0,08-0,5
218-510	CSA	154112-1565656	150	4	28-20
218-510	KEMA	2082146.01	250	6	0,08-0,5
218-510	UR	E45172	150	4	28-20

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected