



Product information



Code No.: **T884E**

Tip cutter - pointed relieved head

- This is the narrowest head shape.
- The underside is relieved and facilitates optimum access even to extremely hard-to-reach areas.

Technical Data

Cut:	Flush
Length:	120 mm / 4,724 Inch
Weight:	81 g / 2.86 oz.
Length of cutting edges:	15 mm / .590 Inch
Head width:	13,5 mm / .531 Inch
Head thickness:	7,5 mm / .295 Inch
Head length:	21 mm / .827 Inch
Max. cutting capability	
Hard wire:	-
Medium hardness:	Ø 0,8 mm / .031 Inch
Copper wire:	Ø 1,6 mm /.062 Inch

Series 800 Maxi

- Maxi-sized cutter for general cutting applications in electronics
- Made from high grade tool steel, cutting edges hardened to Rockwell 63-65 HRc
- Cuts large wire diameters
- Non reflecting surface, ESDsafe and resharpenable

Erem Cutters and Tip Cutters

Internal patented Erem Magic Spring



- Reduce costs by long life
- Constant spring force
- Guarantees more than 1 million operations
- High precision screw joint
 - Smooth jaw action with no play
 - Smooth cutting operation with no jaw overlapping
- Induction-hardened cutting edges in Rockwell hardness 63 65 HRc for exceptionally long life
- EMOS maximum opening stop limits the cutting-edge tips from opening more than 5 mm / .197 lnch. The limited extent to which the handles can open prevent user hand fatigue.
- Ergonomically shaped handles for high comfort, better grip and added safety
- Erem cut:
 Options for semi flush, full flush or super flush cuts