



Male plug-in connector - Horizontal - Stackable version - Pitch 5,08mm - 02÷12 poles

GENERAL INFORMATION

pitch:	5,08 mm
housing height:	7,70 mm
housing depth:	19 mm
dimensional class:	medium
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-40°C ÷ +105°C

ELECTRICAL CHARACTERISTICS

current:	16A
voltage:	250V
impulse voltage:	4 kV

MECHANICAL CHARACTERISTICS

APPROVALS DATA



current:	-	-	UL 1059
voltage:	-	-	22A factory / 20A field
FILE:	-	-	300V
			E178356

MATERIALS

housing: PA - UL 94 V0
 screw: n/a
 clamp/spring: n/a
 terminal: Tin-plated copper alloy

AVAILABLE COLOURS

other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	PF02-5,08-H	N/A	N/A	N/A
03	PF03-5,08-H	N/A	N/A	N/A
04	PF04-5,08-H	N/A	N/A	N/A
05	PF05-5,08-H	N/A	N/A	N/A
06	PF06-5,08-H	N/A	N/A	N/A
07	PF07-5,08-H	N/A	N/A	N/A
08	PF08-5,08-H	N/A	N/A	N/A
09	PF09-5,08-H	N/A	N/A	N/A
10	PF10-5,08-H	N/A	N/A	N/A
11	PF11-5,08-H	N/A	N/A	N/A
12	PF12-5,08-H	N/A	N/A	N/A