



Pushing Performance
Since 1945

D-Sub 15P plast hood 1str-ent slo 4-40 s



Image is for illustration purposes only. Please refer to product description.

Part number	09 67 015 0442 160
Specification	D-Sub 15P plast hood 1str-ent slo 4-40 s
HARTING eCatalogue	https://harting.com/09670150442160

Identification

Category	Hoods / Housings
Series	D-Sub
Type of hood/housing	Shell housing
Description of hood/housing	Cover can be screwed on

Version

Size	D-Sub 2
Version	Top entry
Number of cable entries	1
Cable entry	1x
Cable fixing	Cable clamp
Locking type	With short locking screws Thread 4-40 UNC
2 parts	Yes
Separable	Yes

Technical characteristics

Tightening torque	0.25 Nm Cable clamp screw
	0.25 Nm cover screw
	0.4 Nm Locking screw
Ambient temperature	-20 ... +90 °C
Degree of protection acc. to IEC 60529	IP30
Cable diameter	3.3 ... 8.5 mm



Pushing Performance
Since 1945

Material properties

Material (hood/housing)	Thermoplastic
Colour (hood/housing)	Black
Length	34.7 mm
Width	40 mm
Height	15.2 mm
RoHS	compliant with exemption
RoHS exemptions	6(a)-I: Lead as an alloying element in steel for machining purposes containing up to 0,35 % lead by weight
	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	c3c36a64-4181-41a7-bdc6-2bc2fd6fd011
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

Commercial data

Packaging size	100
Net weight	15.2 g
Country of origin	China
European customs tariff number	85389099
GTIN	5713140221277
eCl@ss	27440213 D-Sub hood
ETIM	EC001133
UNSPSC 24.0	39121416