

SEK 19-34 (4) M-S32-AU KONTAKT



Part number	09 19 034 9643
Specification	SEK 19-34 (4) M-S32-AU KONTAKT
HARTING eCatalogue	https://b2b.harting.com/09190349643

Identification

Category	Connector
Series	SEK Low-profile
Element	PCB transition connectors

Description of the contactStraight

Version

Termination method	Solder termination IDC termination
Connection type	PCB to cable
Number of contacts	34
Details	for IDC flat cable 1.27 mm (0.050") pitch AWG 28/7

Technical characteristics

Contact rows	4
Contact spacing (termination side)	2.54 mm
Contact spacing (mating side)	1.27 mm
Rated current	1 A
Insulation resistance	$\geq 10^{12} \Omega$
Contact resistance	$\leq 20 \text{ m}\Omega$
Limiting temperature	-40 ... +125 °C
Test voltage $U_{r.m.s.}$	0.5 kV

Material properties

Material (insert)	Thermoplastic resin (PC)
Colour (insert)	Beige
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant



Pushing Performance

Material properties

China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Commercial data

Packaging size	52
Net weight	4.54 g
Country of origin	Germany
Customs tariff number	85366953