Automation and Network Solutions






STAK 3 N grau/grey

Industrial Connectors:Rectangular connectors ST-series:Cable socket

Product description	
Description	Cable socket with strain relief
Туре	STAK 3 N grau/grey
Order No.	932 140-106
Type of contact	female
Number of contacts	3 + PE
Cable gland	PG 11
Cable diameter	6 mm to 10 mm
Conductor size	max. 1.5 mm2
Housing Color	grey
Contact bearer color	black
Drawing	



Technical data	
Pin dimensions	2 mm
Rated voltage	DC 250 V / AC 400 V
Rated current	DC 10 A / AC 16 A
Contact resistance	<= 5 mOhm
Type of termination	screw
Material	
Contact material	Cu Zn
Contact surface material	Sn
Contact bearer material	PA
Housing material	PA
Environmental conditions	
Protection class (IEC 60529)	IP 54
Pollution severity	3
Temperature range	-30 °C to +90 °C
Inflammability class	

Housing	UL 94 V-1
Contact bearer	UL 94 HB
Approvals	
UL	UL
VDE	VDE
SEV	SEV
Packaging unit	
Packaging unit	100 pieces
Scope of delivery and accessories	
Accessories to order separately	safety brackets STASI 3

Accessories to order separately

safety brackets STASI 3, order no. 732 045-001