



Single-deck terminal block - Modular version - Pitch 10mm - 1÷2 poles

GENERAL INFORMATION

pitch:	10 mm
housing height:	12,70 mm
housing depth:	9 mm
dimensional class:	medium
wire section:	2.5 mm ² / 14 AWG
clamp opening size:	3.1 × 3.1 mm
wire stripping:	max 6 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	16A
voltage:	750V
test voltage:	3 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

APPROVALS DATA



current:	-	-	UL 1059
voltage:	-	-	20A factory / 15A field
wire section:	-	-	300V
torque:	-	-	14÷30AWG
FILE:	-	-	4.5Lb-in
			E178356

MATERIALS

housing:	PA - UL 94 V0
----------	---------------

AVAILABLE COLOURS

screw:
clamp/spring:
terminal:

Galvanized steel
Tin-plated copper alloy
Copper alloy



other colours:

upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
1	MHE161-10-H	N/A	N/A	N/A
2	MHE162-10-H	N/A	N/A	N/A
..	MHE16..-10-H	N/A	N/A	N/A