

Data sheet

233-210

**PCB TERMINAL STRIP 2 SOLDER PINS / POLE
PIN SPACING 2.5 MM / 0.098 IN WITH PUSH BUTTONS FRONT-ENTRY**



Technical data

Package size 180 4*45 pieces.

Pin spacing from	2.5 mm
Pin spacing from	0.098 in
pole count	10
Cross section from [mm ²]	0.08 mm ²
Cross section to [mm ²]	0.5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	20 AWG
Voltage UL	150 V
Voltage CSA	150 V
Current CSA	4 A
Current UL	4 A
Measured voltage EN	250 V
Measured shock voltage	2.5 kV
Pollution degree	2
Current intensity EN	6 A
Weight	3.95 g
Color	grey
Wiring type	Angled Type
No. of connection Points	10
No. of potentials	10
Height	15.5 mm
Height	0.61 in
Width	27.3 mm

Data sheet

233-210

**PCB TERMINAL STRIP 2 SOLDER PINS / POLE
PIN SPACING 2.5 MM / 0.098 IN WITH PUSH BOTTONS FRONT-ENTRY**

Width	1.075 in
Depth	13.9 mm
Depth	0.547 in
Strip length from	5 mm
Strip length to	6 mm
Strip length	0.22 in

Data sheet

233-210

**PCB TERMINAL STRIP 2 SOLDER PINS / POLE
PIN SPACING 2.5 MM / 0.098 IN WITH PUSH BOTTONS FRONT-ENTRY**

Approval	Voltage	Current	Approval number	Notes
BV	250	6	11915/A0	
CSA	150	4	154112-1465035	
CSM	250	4	017956	
DEMKO	250	4	118980ES	
DEMKO	250	4	DK96-03660	
DNV	250	4	E6998	
GL	250	4	17296-00HH	
KEMA	250	6	90.6212.01/02	
RMR	250	4	99.00007.250	
RosTesT	250	4	B09523	
SEMKO	250		9043004	
UL	150	4	E45172	

Data sheet

233-210

**PCB TERMINAL STRIP 2 SOLDER PINS / POLE
PIN SPACING 2.5 MM / 0.098 IN WITH PUSH BOTTONS FRONT-ENTRY**


Accessories**Item number**

OPERATING TOOL FOR SERIES 233 AND 733	233-332
OPERATING TOOL FOR SERIES 233 AND 733	233-335
SCREWDRIVER Type 1, bar (2,5 x 0,4) mm	210-119
SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 1, bar (2,5 x 0,4) mm	210-619
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 2.5MM; SERIES 233, 234, 733	249-151
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 2.5MM; SERIES 233, 234, 733	249-152
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 2.5MM; SERIES 233, 234, 733	249-153

Data sheet

233-210

PCB TERMINAL STRIP 2 SOLDER PINS / POLE
PIN SPACING 2.5 MM / 0.098 IN WITH PUSH BUTTONS FRONT-ENTRY



Data sheet

233-210

**PCB TERMINAL STRIP 2 SOLDER PINS / POLE
PIN SPACING 2.5 MM / 0.098 IN WITH PUSH BOTTONS FRONT-ENTRY**

Diameter of drilled hole: $1,1^{+0,1}$ mm
L = (No.of poles x pin spacing) + 2,3 mm