

Standoffs Type B Female- / Male

- **Material** – Steel
- Stainless steel
- Brass


DIN 1.0718
DIN 1.4305
DIN 2.0402

- **Plating DIN 267**
 - zinc plated 5 µm (A2E)
 - yellow chromated 8 µm(A3G)
 - nickel plated 3 µm (E1E)

UNC 4-40 / M 2,5
UNC 4-40 / M 3
UNC 4-40 / UNC 4-40



- **Tolerances**
 - Hex length DIN 7168 middle (in middle ± 0,15 mm)
 - Outside length ca. ± 0,25 mm
 - Thread DIN 13 Part 13
 - Undercut DIN 76



Thread		Dimensions in mm			Order-No.						
GA	GI	L	min. 2,6 I	A	Steel zinc pl. SW 5	Steel y. chrom. SW 5	Brass nickel pl. SW 5	Steel stainless SW 5	Steel zinc pl. SW 4,75	Steel stainless SW 4,75	under- cut
M 2,5	UNC 4-40	5,0	3,4	8,0	9.24.751	5.17.244					no
M 2,5	UNC 4-40	5,4	3,8	7,5		5.17.254					yes
M 3	UNC 4-40	5,0	3,5	6,0	9.34.651						no
M 3	UNC 4-40	5,0	3,4	6,0		5.17.344					yes
M 3	UNC 4-40	5,0	3,4	8,0	9.34.751	5.17.354	9.34.853				no
M 3	UNC 4-40	4,8	3,1	6,0		5.17.348 ⁺					yes
M 3	UNC 4-40	5,0	3,4	12,0	9.34.851	5.17.393					no
M 3	UNC 4-40	6,1	4,0	5,5	9.34.657	5.17.364					yes
M 3	UNC 4-40	7,0	4,5	5,5		5.17.374					yes
M 3	UNC 4-40	7,0	7,0	5,5	9.34.571						yes
M 3	UNC 4-40	8,5	6,0	8,0	9.34.581						yes
UNC 4-40	M 2,5	5,0	3,4	8,0	9.42.851						no
UNC 4-40	M 3	5,0	3,2	6,0	9.43.651	5.17.436					no
UNC 4-40	M 3	5,0	3,2	8,0	9.43.752	5.17.438	9.43.753				no
UNC 4-40	M 3	5,0	3,2	12,0		5.17.439					no
UNC 4-40	UNC 4-40	4,0	3,0	5,0			9.44.443				no
UNC 4-40	UNC 4-40	5,0	3,1	5,9			9.44.543				no
UNC 4-40	UNC 4-40	4,9	3,1	6,3					9.44.641	9.44.649	no
UNC 4-40	UNC 4-40	4,9	3,1	8,0					9.44.741		no
UNC 4-40	UNC 4-40	4,9	3,1	12,5					9.44.841	9.44.849	no
UNC 4-40	UNC 4-40	4,9	3,4	7,9	9.44.747	5.17.444 [*]				9.44.749	no
UNC 4-40	UNC 4-40	4,9	3,9	14,2		5.17.448 [*]					no
UNC 4-40	UNC 4-40	4,8	3,4	3,9	9.44.351	5.17.457					no
UNC 4-40	UNC 4-40	4,9	3,4	5,9	9.44.541						
UNC 4-40	UNC 4-40	4,9	3,1	6,4	9.44.641						
UNC 4-40	UNC 4-40	5,0	3,4	6,0	9.44.651	5.17.456					no
UNC 4-40	UNC 4-40	5,0	3,4	6,0			9.44.653				yes
UNC 4-40	UNC 4-40	4,9	3,4	8,0	9.44.741						no
UNC 4-40	UNC 4-40	5,0	3,4	8,0	9.44.751	5.17.454			9.44.842		no
UNC 4-40	UNC 4-40	5,0	3,4	8,0			9.44.753	9.44.759			yes
UNC 4-40	UNC 4-40	5,0	3,4	12,0	9.44.851	5.17.458					no
UNC 4-40	UNC 4-40	4,9	3,4	12,5	9.44.841						
UNC 4-40	UNC 4-40	6,1	4,1	6,0	9.44.661						no

⁺ St ycr, SW 4,5

^{*} SW 4,75