



Multi-deck terminal block - Modular version - Pitch 5,08 - 2÷3 poles

GENERAL INFORMATION

pitch:	5,08 mm
housing height:	19,50 mm
housing depth:	8.6 mm
dimensional class:	slow
wire section:	1.5 mm ² / 16 AWG
clamp opening size:	2.5 × 2 mm
wire stripping:	max 6 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	13.5A
voltage:	250V
test voltage:	2 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

APPROVALS DATA



current:

-

-

UL 1059
13.5A factory / 10A field

voltage:

-

-

300V

wire section:

-

-

16÷30AWG

torque: - - 4.5Lb-in
FILE: - - E178356

MATERIALS

housing: PA - UL 94 V0
screw: Galvanized steel
clamp/spring: Nickeled copper alloy
terminal: Tin-plated copper alloy

AVAILABLE COLOURS



other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MMT152-5,08-V	N/A	N/A	N/A
3	MMT153-5,08-V	N/A	N/A	N/A
..	MMT15..-5,08-V	N/A	N/A	N/A