



E3AS-HL150MT M3

Photoelectric sensor, rectangular housing, stainless steel, red laser class 1, background suppression, spot beam, 35-150 mm, 10-30 VDC, PNP, Light-ON/Dark-ON, IO-Link COM3, M8 connector 4-pin

Specifications

Shape	Cuboid
Sensing method	Background suppression
Sensing distance	150 mm
Sensing distance (min.)	35 mm
Setting method	IO-Link, Teach-In
Connection method	Connector M8 - 4 pin
Output type	IO-Link, PNP
Operation mode	Dark-ON, Light-ON
IO-Link baud rate	COM3 (230.4 kbps)
Response time	1.5 ms
Material housing	Stainless steel
Product Width (unpacked)	15.5 mm
Product Height (unpacked)	48.6 mm
Product Depth (unpacked)	28.9 mm
Type of light	Laser diode, red light
Laser class	1
Spot size	2.5 mm x 1.3 mm
Power supply voltage	10-30 V



E39-E16

Air blow unit



E39-E19

Front protection cover for E3AS-HL



E39-L223

Rear mounting bracket



E39-L231

L-shaped mounting bracket



E39-L232

Horizontal protective cover bracket



E39-L234

Robust mounting bracket



E39-L261

Flexible mounting bracket



E39-L262

50mm post for flexible mounting bracket E39-L261



E39-L263

100mm post for flexible mounting bracket E39-L261



M8 Connectors & Cordsets

Industrial connectors & cordsets for any application

Downloads

CAD Library



E3AS – Automotive Brochure

EN PDF 18.7 MB



E3AS – Food & Commodities Datasheet

EN PDF 18.1 MB



E3AS-HL Instruction Sheet

EN PDF 7.9 MB



E3AS-HL Index list

EN PDF 1.34 MB



E3AS-HLxxx[x]xx IO-Link IODD file

EN ZIP 1.15 MB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



IO-Link Series Brochure

EN PDF 8.05 MB

