



Data sheet Product SL 22 139 ...



Features

grid:	2.54 mm
no. of contacts:	2 / 4 / 6 / 8 / 10 / 12 / 14 / 16 / 18 / 20 / 22 / 24 / ... / 72
contact material:	CuSn alloy
surface of contact:	<ul style="list-style-type: none">• selective gold-plated• gold-plated• tin-plated
surface contact / contact sleeve:	<ul style="list-style-type: none">• Ni+≥0.2µm Au• Ni+4...6µm Sn
version:	standard
volume resistance:	≤5 mΩ
nominal current:	3 A
nominal voltage:	250 V AC
test voltage:	2000 V
insulating body material:	PA 4.6. GF
temperature range:	<ul style="list-style-type: none">• -40°C... +163°C• (260°C/10 s)
class of inflammability:	UL 94 V-0
specific insulation resistance:	>10⁷ Ω·m
connection type:	THT (soldering)
reflow solderable:	yes

Technical Drawing



A:	13.9 mm
B:	3 mm
C:	8.1 mm
S:	5.0 mm

Fischer Elektronik GmbH & Co. KG
DEUTSCHLAND • GERMANY • ALLEMAGNE

Nottebohmstraße 28
58511 Lüdenscheid

Telefon +49 2351 435-0
Telefax +49 2351 45754

info@fischerelektronik.de
www.fischerelektronik.de