

Item no.: 232-235/039-000
 Product description: FEMALE CONNECTOR WITH RIGHT ANGLED SOLDER PIN
 5 POLE WITH LOCKING LEVER PIN SPACING 5 MM / 0.197
 IN WITH CODING FINGERS MATING DIRECTION PARALLEL
 TO PCB WITH INTEGRATED FIXING FLANGES SOLDER PIN
 0.6x1 MM



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

Weight	5.5 g
Color	gray
pole count	5
Height	11.6 mm
Height	0.457 in
Width	40.8 mm
Width	1.606 in
Depth	18.25 mm
Depth	0.719 in
Pin spacing from	5 mm
Pin spacing from	0.197 in
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	4 kV
Current intensity EN	12 A
Pollution degree	2

Measured voltage EN	630 V
Measured shock voltage	4 kV
Current intensity EN	12 A
Material group	I
Contact material	Copper base alloy
Contact surface	tin-plated



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
232-235/039-000	ABS	04-HG469925/1-PDA	250	12	0,08-2,5
232-235/039-000	GL	17296-00HH	250	12	0,08-2,5
232-235/039-000	LR	96/20035	250	12	0,08-2,5

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected