



**MATERIAL**

Insulator : NY6T UL94-V0

Contact Pin : Phosphor Bronze

**SPECIFICATION**

Current Rate : 3 AMP

Insulation Resistance : 5000mΩMin.

Contact Resistance : 20mΩMax.

Dielectric Voltage : AC 500V for one minute

Operating Temperature: -40°C to +105°C

61H-9  $\frac{2}{1}$ -  $\frac{xx}{3}$   $\frac{T}{4}$   $\frac{B}{5}$   $\frac{61}{6}$

1. 7: Green Product
- 9: Green Product High Temp
2. 1: Single row
- 2: Dual rows
3. No. of contacts per row
4. G: Gold flash
- T: Tin plated
5. B: Black Insulator
6. Pinrex internal code.

POLES	DIM E	DIM F	POLES	DIM E	DIM F
			21	53.84	50.80
2	5.58	2.54	22	56.38	53.34
3	8.12	5.08	23	58.92	55.88
4	10.66	7.62	24	61.46	58.42
5	13.20	10.16	25	64.00	60.96
6	15.74	12.70	26	66.54	63.50
7	18.28	15.24	27	69.08	66.04
8	20.82	17.78	28	71.62	68.58
9	23.36	20.32	29	74.16	71.12
10	25.90	22.86	30	76.70	73.66
11	28.44	25.40	31	79.24	76.20
12	30.98	27.94	32	81.78	78.74
13	33.52	30.48	33	84.32	81.28
14	36.06	33.02	34	86.86	83.82
15	38.60	35.56	35	89.40	86.36
16	41.14	38.10	36	91.94	88.90
17	43.68	40.64	37	94.48	91.44
18	46.22	43.18	38	97.02	93.98
19	48.76	45.72	39	99.56	96.52
20	51.30	48.26	40	102.1	99.06



REV.	DESCRIPTION	DATE
A	RELEASE	2023/06/13

**TOLERANCE**

.0 =±.30  
.00 =±.20  
.000 =±.XXX  
.0000=±.  
ANG.=±3'

UNITS : mm

SCALE NONE SIZE A4

OLD PART NO.

DRAWER 罗尚尚 CHECK 李剑

SHEET 1 OF 1 REV. A APP'D 李剑

TITLE FEMALE HEADER 2.54\*2.54mm STRAIGHT TYPE, DUAL ROWS HEIGHT 8.5mm

NEW PART NO. 61H-92-xxTB61

**频锐科技股份有限公司**  
PINREX TECHNOLOGY CORP.

DRAW NO. 61H-92-xxTB61