



## Single-deck terminal block - Modular version - Pitch 10mm - 1÷6 poles

### GENERAL INFORMATION

pitch:	10 mm
housing height:	10,60 mm
housing depth:	8.1 mm
dimensional class:	slow
wire section:	1.5 mm <sup>2</sup> / 16 AWG
clamp opening size:	2.6 × 2 mm
wire stripping:	max 6 mm
operating temperature:	-40°C ÷ +130°C

### ELECTRICAL CHARACTERISTICS

current:	13.5A
voltage:	750V
test voltage:	3 kVrms/60s

### MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

### APPROVALS DATA



EN 60998-1



-



UL 1059

13.5A factory / 10A field

current:	13.5A	-	-
voltage:	750V	-	-
wire section:	1.5mm <sup>2</sup>	-	-
torque:	0.5Nm	-	-
FILE:	EQ202	-	-

600V  
16÷30AWG  
4.5Lb-in  
E178356

### MATERIALS

housing:	PA - UL 94 V0
----------	---------------

### AVAILABLE COLOURS

screw:  
clamp/spring:  
terminal:

Galvanized steel  
Nicked copper alloy  
Tin-plated copper alloy



other colours:

upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
1	MV151-10-H	N/A	N/A	N/A
2	MV152-10-H	N/A	N/A	N/A
3	MV153-10-H	N/A	N/A	N/A
4	MV154-10-H	N/A	N/A	N/A
5	MV155-10-H	N/A	N/A	N/A
6	MV156-10-H	N/A	N/A	N/A
..	MV15..-10-H	N/A	N/A	N/A