


Data sheet

282-870

**DISCONNECT TERMINAL BLOCK FOR TEST PURPOSES CENTRE MARKING
CARRIER RAIL DIN 35 FRONT-ENTRY CAGE CLAMP CONNECTION**



Technical data

Package size 20 pieces.

| | |
|---------------------------------------|---------------------|
| Cross section from [mm ²] | 0.2 mm ² |
| Cross section to [mm ²] | 6 mm ² |
| Cross section from [AWG] | 24 AWG |
| Cross section to [AWG] | 10 AWG |
| Voltage UL | 600 V |
| Current UL | 30 A |
| Measured voltage EN | 500 V |
| Measured shock voltage | 6 kV |
| Pollution degree | 3 |
| Current intensity EN | 30 A |
| Weight | 48.221 g |
| Color | grey |
| Wiring type | Angled Type |
| No. of connection Points | 3 |
| No. of potentials | 2 |
| Height | 75 mm |
| Height | 2.95 in |
| Width | 8 mm |
| Width | 0.315 in |
| Depth | 122 mm |
| Depth | 4.8 in |
| Strip length from | 12 mm |
| Strip length to | 13 mm |

Data sheet**282-870****DISCONNECT TERMINAL BLOCK FOR TEST PURPOSES CENTRE MARKING
CARRIER RAIL DIN 35 FRONT-ENTRY CAGE CLAMP CONNECTION**

Strip length**0.49 in**

Data sheet

282-870

DISCONNECT TERMINAL BLOCK FOR TEST PURPOSES CENTRE MARKING CARRIER RAIL DIN 35 FRONT-ENTRY CAGE CLAMP CONNECTION

| Approval | Voltage | Current | Approval number | Notes |
|----------|---------|---------|-------------------|-------|
| BV | 500 | 30 | 07436/Co | |
| CCA | 500 | 30 | NL5448 | |
| DNV | 500 | 30 | E6999 | |
| GL | 500 | 30 | 17295-00HH | |
| KEMA | 500 | 30 | 98.2759.05 | |
| LR | 500 | 30 | 91/20112(E1) | |
| PRS | 500 | 30 | TE/1219/880590/98 | |
| RMR | 500 | 30 | 99.00007.250 | |
| RosTesT | 500 | 30 | B09523 | |
| UL | 600 | 30 | E45172 | |

Data sheet

282-870

DISCONNECT TERMINAL BLOCK FOR TEST PURPOSES CENTRE MARKING CARRIER RAIL DIN 35 FRONT-ENTRY CAGE CLAMP CONNECTION

| Accessories | Item number |
|--|-------------------------------|
| ADJACENT JUMPER NOMINAL CURRENT 41 A | 282-402 |
| ADJACENT JUMPER NOMINAL CURRENT 41 A | 282-424 |
| ALTERNATE JUMPER NOMINAL CURRENT 41 A | 282-409 |
| ALUMINIUM CARRIER RAIL 35 X 7.5 MM, 1.5 MM / 0.059 IN THICK | 210-196 |
| CARRIER FOR SPARE ADJACENT JUMPERS SUITABLE FOR ADJACENT JUMPER SERIES 279-284, BANANENSTECKER SERIES 215 | 209-100 |
| COPPER CARRIER RAIL 35 X 15 MM, 2.3 MM / 0.091 IN THICK | 210-198 |
| COVER CARRIER TYPE 2 | 709-168 |
| COVER TYPE 2 | 709-154 |
| END AND SEPARATOR PLATE 1.5 MM / 0.059 IN THICK | 282-386 |
| END AND SEPARATOR PLATE 1.5 MM / 0.059 IN THICK | 282-387 |
| END AND SEPARATOR PLATE 1.5 MM / 0.059 IN THICK | 282-391 |
| END AND SEPARATOR PLATE 1.5 MM / 0.059 IN THICK | 282-392 |
| GROUP MARKER CARRIER FOR SERIES 282 BLOCKS | 209-143 |
| GROUP MARKER CARRIER FOR SERIES 282 BLOCKS | 209-144 |
| HOLD BLOCK FOR ISOLATED MOUNTING ON DIN 35 RAIL | 209-106 |
| Individual wire jumpers | individual jumper |
| LOCK OUT FOR DISCONNECT LINK | 282-384 |
| LOCKING COVER FOR MECHANICAL LOCKING OF SEVERAL LINKS | 282-881 |
| LOCKING COVER FOR MECHANICAL LOCKING OF SEVERAL LINKS | 282-882 |
| LOCKING COVER FOR MECHANICAL LOCKING OF SEVERAL LINKS | 282-883 |
| LOCKING COVER FOR MECHANICAL LOCKING OF SEVERAL LINKS | 282-884 |
| LOCKING PROFILE FOR MECHANICAL LOCKING OF SEVERAL LINKS | 210-254 |
| Open individual wire jumpers ends | individual jumper open end |
| OPERATING STICKER | 210-412 |
| OPERATING STICKER FOR FRONT-ENTRY RAIL-MOUNTED TERMINAL BLOCKS, ANGLED TYPE | 210-183 |
| PIVOTABLE GROUP MARKER CARRIER | 249-105 |
| PROTECTIVE WARNING MARKER WITH HIGH VOLTAGE SYMBOL, BLACK | 282-415 |
| SCREWDRIVER Type 3, bar (5,5 x 0,8) mm | 210-121 |
| SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 3, bar (5,5 x 0,8) mm | 210-621 |
| SCREWLESS END STOP 10 MM / 0.394 IN WIDE | 249-117 |
| SCREWLESS END STOP 6 MM / 0.236 IN WIDE | 249-116 |
| SPARE FIXING / RETAINING SCREWS | 209-196 |
| SPARE KNURLED NUT | 210-549 |
| STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK | 210-114 |
| STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK | 210-197 |
| STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK | 210-506 |
| STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK | 210-508 |

Data sheet

282-870

DISCONNECT TERMINAL BLOCK FOR TEST PURPOSES CENTRE MARKING CARRIER RAIL DIN 35 FRONT-ENTRY CAGE CLAMP CONNECTION

| | |
|--|-----------------|
| STEEL CARRIER RAIL 35 X 15 MM, 2.3 MM / 0.091 IN THICK | 210-118 |
| STEEL CARRIER RAIL 35 X 15 MM, 2.3 MM / 0.091 IN THICK | 210-548 |
| STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK | 210-112 |
| STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK | 210-113 |
| STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK | 210-162 |
| STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK | 210-229 |
| STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK | 210-504 |
| STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK | 210-505 |
| TEST PLUG FOR TEST PLUG 4 MM / 0.157 IN Ø | 209-170 |
| WCB COMBI MARKING SYSTEM PLAIN | 249-200 |
| WIRE COMMONING CHAIN INSULATED | 210-103 |
| WIRE COMMONING CHAIN INSULATED | 210-123 |
| WIRE COMMONING CHAIN INSULATED | 709-110 |
| WIRE COMMONING CHAIN INSULATED | 709-111 |
| WIRE COMMONING CHAIN INSULATED | 709-112 |
| WSB QUICK MARKING SYSTEM PLAIN | 209-501 |
| WSB QUICK MARKING SYSTEM PLAIN | 209-501/000-002 |
| WSB QUICK MARKING SYSTEM PLAIN | 209-501/000-005 |
| WSB QUICK MARKING SYSTEM PLAIN | 209-501/000-006 |
| WSB QUICK MARKING SYSTEM PLAIN | 209-501/000-007 |
| WSB QUICK MARKING SYSTEM PLAIN | 209-501/000-012 |
| WSB QUICK MARKING SYSTEM PLAIN | 209-501/000-017 |
| WSB QUICK MARKING SYSTEM PLAIN | 209-501/000-023 |
| WSB QUICK MARKING SYSTEM PLAIN | 209-501/000-024 |