Miniature Power Relays

CSM_MY-GS_DS_E_10_1

Mechanical Indicators Added as a Standard Feature to Our Best-selling MY General-purpose Relays

- A lineup of models with latching levers added for easier circuit checking.
- Reduces wiring work by 60% when combined with the PYF-PU Push-In Plus Socket (according to actual OMRON measurements).
- Relays with AC and DC coils have different colors of operating indicators (LEDs).
- Printing on the coil tape indicates the operating coil specification.
- Mechanical operation indicators are a standard feature on all models.
- UL, CSA, IEC (VDE certification), CQC and Lioyd.

Refer to the Common Relay Precautions.

Features

Common to all specifications

- Mechanical indicators are a standard feature on all models so that you can easily check the contact status.
- The color of the LED shows whether the coil voltage is AC or DC.

Mechanical indicators (one on left and one on right) Contacts ON (coil energized)

Contacts OFF (coil de-energized)



Relay with AC Coil (LED: Red)



Relay with AC Coil (LED: Red)



Relay with DC Coil (LED: Green)

With latching leverUseful for the operation check of relay sequence circuits.

• The coil voltage AC/DC can be identified by the color of the latching lever (AC coil specification: red, DC coil specification: Blue).

Latching lever operating method

	Normal State	Mode 1: Momentary State	Mode 2: Locked State
When seen from the top		Yellow button	
When seen from the side			
Operation Description		Slide the lever one step and press the yellow button with an insulated tool to operate the contacts.	If you slide the lever two steps, the contacts lock in the operation position.



Model Number Structure

Model Number Legend MY ⁻/₁ ⁻/₂ ⁻/₃ ⁻/₄ ⁻/₄ ⁻/₅ ⁻/₅

List of Models

Miniature Power Relays (MY-GS-R)

			Plug-in (octal pins) terminals			
Catagony	Number	Contact structure	L _{TT}	With operation indicator		
Category	of poles				With latching lever	
		2		MY2-GS-R	MY2N-GS-R	MY2IN-GS-R
Stanuaru mouers	4	-	MY4-GS-R	MY4N-GS-R	MY4IN-GS-R	
	Type 1	2			MY2N-D2-GS-R	MY2IN-D2-GS-R
Models with built-in diodes	13 A1 A2	4	Single		MY4N-D2-GS-R	MY4IN-D2-GS-R
for coil surge absorption	Type 2	2			MY2N-D1-GS-R	MY2IN-D1-GS-R
	13 14 A1 A2	4			MY4N-D1-GS-R	MY4IN-D1-GS-R
Models with built-in CR circuits for coil surge absorption		2	_		MY2N-CR-GS-R	MY2IN-CR-GS-R
		4			MY4N-CR-GS-R	MY4IN-CR-GS-R

Ordering Information

Main unit Standard model without operation indicator

Number of poles	Model	Rated voltage (V)					
2	MY2-GS-R	12, 24, 48, 100/110, 110/120, 200/220, 220/240 VAC 6, 12, 24, 48, 100/110 VDC					

4 MY4-GS-R 12, 24, 48, 100/110, 110/120, 200/220, 220/240 VAC 6, 12, 24, 48, 100/110 VDC

Standard model with operation indicator

Number of poles	Model	Rated voltage (V)	
2	MY2N-GS-R	12, 24, 48, 100/110, 110/120, 200/220, 220/240 VAC 6, 12, 24, 48, 100/110, 220 VDC	
4	MY4N-GS-R	12, 24, 48, 100/110, 110/120, 200/220, 220/240 VAC 6, 12, 24, 48, 100/110, 220 VDC	

Standard model with operation indicator and latching lever

Number of poles	Model	Rated voltage (V)
2	MY2IN-GS-R	12, 24, 48, 100/110, 110/120, 200/220, 220/240 VAC 6, 12, 24, 48, 100/110, 220 VDC
4	MY4IN-GS-R	12, 24, 48, 100/110, 110/120, 200/220, 220/240 VAC 6, 12, 24, 48, 100/110, 220 VDC

Models with built-in diodes for coil surge absorption with operation indicator (14: +)

Number of poles	Model	Rated voltage (V)		
2	MY2N-D2-GS-R	12, 24, 48, 100/110, 220 VDC		
4	MY4N-D2-GS-R	12, 24, 48, 100/110, 220 VDC		

Models with built-in diodes for coil surge absorption with operation indicator (13: +)

Number of poles	Model	Rated voltage (V)
2	MY2N-D1-GS-R	12, 24, 48, 100/110 VDC
4	MY4N-D1-GS-R	12, 24, 48, 100/110 VDC

Models with built-in diodes for coil surge absorption with operation indicator and latching lever (14: +)

Number of poles	Model	Rated voltage (V)		
2	MY2IN-D2-GS-R	12, 24, 48, 100/110, 220 VDC		
4	MY4IN-D2-GS-R	12, 24, 48, 100/110, 220 VDC		

Models with built-in diodes for coil surge absorption with operation indicator and latching lever (13: +)

Number of poles	Model	Rated voltage (V)
2	MY2IN-D1-GS-R	12, 24, 48, 100/110 VDC
4	MY4IN-D1-GS-R	12, 24, 48, 100/110 VDC

Models with built-in CR circuits for coil surge absorption with operation indicator

Number of poles Model		Rated voltage (V)		
2	MY2N-CR-GS-R	100/110, 110/120, 200/220, 220/240 VAC		
4	MY4N-CR-GS-R	100/110, 110/120, 200/220, 220/240 VAC		

Models with built-in CR circuits for coil surge absorption with operation indicator and latching lever

Number of poles	Model	Rated voltage (V)		
2	MY2IN-CR-GS-R	100/110, 110/120, 200/220, 220/240 VAC		
4	MY4IN-CR-GS-R	100/110, 110/120, 200/220, 220/240 VAC		

Ratings and Specifications

Ratings

Main unit

Operating Coil

ltem Rated voltage		Rated current (mA)		Coil Coi resistance	Coil indu	ctance (H)	Must-operate voltage	Must-release voltage	Maximum voltage	Power consumption
		50 Hz	60 Hz	(Ω)	Armature OFF	Armature ON	Perce	ntage of rated voltage		(VA, Ŵ)
	12	106.5	91	46	0.17	0.33			- 110%	
	24	53.8	46	180	0.69	1.3	-			
	48	25.7	21.1	788	3.22	5.66	-			Approx. 0.9 to 1.3 (at 60 Hz)
AC	100/110	11.7/12.9	10.0/11.0	3,750	14.54	24.6	- - - 80% max. * 1	30% min. * 2		
	110/120	9.9/10.8	8.4/9.2	4,430	19.2	32.1				
	200/220	6.2/6.8	5.3/5.8	12,950	54.75	94.07				
	220/240	5.2/6.2	4.3/5.0	15,920	83.5	136.4				
	6	146 (151)		41.0 (39.8)	0.17	0.33				
	12	72.7 (75)	72.7 (75)		0.73	1.37	-			Approx 0.9
	24	36.3 (37.7)	36.3 (37.7)		3.2	5.72				
DC	48	17.6 (18.8)		2,725 (2,560)	10.6	21.0		10% min. * 2		Appiox. 0.9
	100/110	8.7 (9.0)/9.6	6 (9.9)	11,440 (11,100)	45.6	86.2				
	220	3.6		60,394	362.3	452.9				Approx. 0.8

Note: 1. The rated current and coil resistance are measured at a coil temperature of 23°C with tolerances of +15%/–20% for the AC rated current and +15% for the DC coil resistance.

2. The AC coil resistance and inductance values are reference values only (at 60 Hz).

3. Operating characteristics were measured at a coil temperature of 23°C.

4. The values in parentheses for the rated currents and coil voltages of DC coils are for models with LED operation indicators.

5. The maximum voltage capacity was measured at an ambient temperature of 23°C.

***1.** There is variation between products, but actual values are 80% max.

The Relay will operate if 80% or higher of the rated voltage is applied. However, to achieve the specified characteristics, apply the rated voltage to the coil.

***2.** There is variation between products, but actual values are 30% minimum for AC and 10% minimum for DC. To ensure release, use a value that is lower than the specified value.

Contacts

	2 poles				4 poles		
	Resistive	eload	Inductive load (cos φ = 0.4, L/R = 7 ms)	Resisti	ive load	Inductive load (cos ∳ = 0.4, L/R = 7 ms)	
Contact configuration	DPDT			4PDT			
Contact structure	Single						
Contact material	Ag	Ag					
Rated load	10 A at 250 VAC 10 A at 30 VDC	5 A at 220 VAC 5 A at 24 VDC	2 A at 220 VAC 2 A at 24 VDC	6 A at 250 VAC 6 A at 30 VDC	3 A at 220 VAC 3 A at 24 VDC	0.8 A at 220 VAC 1.5 A at 24 VDC	
Electrical endurance *1	100,000 operations 500,000 operations			30,000 operations 200,000 operations			
Rated carry current	10 A			6 A *2			
Maximum contact voltage	250 VAC, 220 VDC			250 VAC, 220 VDC			
Maximum contact current	10 A			6 A *2			
Maximum switching capacity	2,500 VA 300 W		440 VA 48 W	1,500 VA 180 W		176 VA 36 W	
Minimum load (reference values) *3	1 mA at 5 VDC		•			·	

*1. Rated load, switching frequency: 2,400 operations/h. Ambient temperature condition: 23°C. Duty ratio: 33%.

*2.4 poles of 6 A is for an ambient temperature of 50°C. At an ambient temperature of 70°C, the value is 3 A.

*3. These values are guides for the switchable limits for minute load levels, such as in electronic circuits. Actual characteristics may be different. These values will depend on the switching frequency, atmosphere, and expected reliability level. Confirm applicability in the actual system under actual application conditions.

Characteristics Main unit

		2 poles	4 poles	
Contact resistance *1		100 mΩ max.		
Operation time *2		20 ms max.		
Release time *2		20 ms max.		
Maximum operating Mechanical		18, 000 operations/h		
frequency	Rated load	2,400 operations/h		
Insulation resistance *	<3	1,000 MΩ min.		
Between coil and contacts		2,000 VAC at 50/60 Hz for 1 min.		
Dielectric strength	Between contacts of different polarity	2,000 VAC at 50/60 Hz for 1 min.		
	Between contacts of the same polarity	1,000 VAC at 50/60 Hz for 1 min.		
Vibration resistance	Destruction	10 to 55 to 10 Hz, Double amplitude: 1.0 mm		
VIDIATION TESIStance	Malfunction	10 to 55 to 10 Hz, Double amplitude: 1.0 mm		
Shock resistance	Destruction	1,000 m/s ² (approx. 100 G)		
Shock resistance	Malfunction	200 m/s ² (Approx. 20 G)		
Mechanical endurance		50,000,000 operations (switching frequency: 18,000 operations/h)		
Ambient operating temperature		Standard models: –55 to 70°C (with no icing or condensation) Models with LED operation indicators: –40 to 70°C (with no icing or condensation)		
Ambient humidity		5% to 85%		
Weight		Approx. 35 g		

Note: The above values are initial values.

*1. Measurement conditions: 1 A at 5 VDC using the voltage drop method.
*2. Measurement conditions: With rated operating power applied, not including contact bounce time.

*3. Measurement conditions: For 500 VDC applied to the same location as for dielectric strength measurement.

Certified Ratings for Models Certified for Safety Standards

The rated values for safety standard certification are not the same as individually defined performance values. Always check the specifications before use.

Main unit

UL-certified Models: UL508

MY-GS	Number of poles	Coil ratings	Contact ratings	Certified number of operations
	2	12 VAC, 24 VAC, 48 VAC, 100/110 VAC, 110/120 VAC, 200/220 VAC, or 220/240 VAC 6 VDC, 12 VDC, 24 VDC, 48 VDC, 100/110 VDC, or 220 VDC	5 A, 30 VDC (General Use) 10 A, 30 VDC (General Use) 5 A, 250 VAC (General Use) 10 A, 250 VAC (General Use)	6,000 operations
	4	12 VAC, 24 VAC, 48 VAC, 100/110 VAC, 110/120 VAC, 200/220 VAC, or 220/240 VAC 6 VDC, 12 VDC, 24 VDC, 48 VDC, 100/110 VDC, or 220 VDC	3 A, 30 VDC (General Use) 6 A, 30 VDC Resistive Load 3 A, 250 VAC (General Use) 6 A, 250 VAC Resistive Load	6,000 operations

CSA-certified Models: CSA C22.2 No.14

MY-GS	Number of poles	Coil ratings	Contact ratings	Certified number of operations
	2	12 VAC, 24 VAC, 48 VAC, 100/110 VAC, 110/120 VAC, 200/220 VAC, or 220/240 VAC 6 VDC, 12 VDC, 24 VDC, 48 VDC, 100/110 VDC, or 220 VDC	5 A, 30 VDC (General Use) 10 A, 30 VDC (General Use) 5 A, 250 VAC (General Use) 10 A, 250 VAC (General Use)	6,000 operations
	4	12 VAC, 24 VAC, 48 VAC, 100/110 VAC, 110/120 VAC, 200/220 VAC, or 220/240 VAC 6 VDC, 12 VDC, 24 VDC, 48 VDC, 100/110 VDC, or 220 VDC	3 A, 30 VDC (General Use) 6 A, 30 VDC Resistive Load 3 A, 250 VAC (General Use) 6 A, 250 VAC Resistive Load	6,000 operations

VDE-certified Models: EN 61810-1

MY-GS	Number of poles	Coil ratings	Contact ratings	Certified number of operations
	2	12 VAC, 24 VAC, 48 VAC, 100/110 VAC, 110/120 VAC, 200/220 VAC, or 220/240 VAC 6 VDC, 12 VDC, 24 VDC, 48 VDC, 100/110 VDC, or 220 VDC	10 A, 30 VDC (L/R = 0) 10 A, 250 VAC (cosφ = 1)	10,000 operations
	4	12 VAC, 24 VAC, 48 VAC, 100/110 VAC, 110/120 VAC, 200/220 VAC, or 220/240 VAC 6 VDC, 12 VDC, 24 VDC, 48 VDC, 100/110 VDC, or 220 VDC	6 A, 30 VDC (L/R = 0) 6 A, 250 VAC (cosφ = 1)	10,000 operations

CQC-certified Models

Model	Standard number	Certification No.
MY-GS	GB/T 21711.1	CQC18002198531

LR certification (Lloyd's Register)

Model	Environmental Category	Operating Coil ratings
MY-GS-R	ENIV2 3	12 to 240 VAC
WI-00-IX	LINVZ, S	6 to 220 VDC

Engineering Data (Reference Value)

Maximum Switching Capacity MY2□□-□□-GS-R (AC load)



MY4□□-□□-GS-R (AC load)



MY2□□-□□-GS-R (DC load)



MY4□□-□□-GS-R (DC load)



Endurance Curve MY2□□-□□-GS-R (Resistive Load)



MY40----GS-R (Resistive Load)



Note: 1. Number of operations: AC load, 50 Hz, 80% 2. Switching condition: NO or NC



MY40---GS-R (Inductive Load)



Ambient Temperature vs. Must-operate and Must-release Voltage MY2D-D-GS-R AC Models MY2D





Ambient Temperature vs. Coil Temperature Rise MY2□□-□□-GS-R AC Models, 50 Hz







MY4□□-□□-GS-R DC Models



MY2DD-DD-GS-R DC Models



MY400-00-GS-R DC Models



MY-GS

Dimensions

(Unit: mm)

Relays



Terminal Arrangement/Internal Connections (Bottom View)

MY2-GS-R		MY2⊡N-GS-R		MY2⊡N-	D2-GS-R
Standard Models	AC Models	DC Models (except 220 VDC)	DC Models (for 220 VDC)	DC Models (except 220 VDC)	DC Models (for 220 VDC)
$\begin{bmatrix} 1 & 4 \\ 5 & 8 \\ 9 & 12 \\ \hline 13 & 14 \end{bmatrix}$					
(The coil has no polarity.)	(The coil has no polarity.)	(The coil has no polarity.)	(The coil has no polarity.)	(The coil has polarity.)	(The coil has polarity.)

MY2⊡N-	MY2□N-D1-GS-R		
DC Models (except 220 VDC)	DC Models (for 220 VDC)	AC Models	
(The coil has polarity.)	(The coil has polarity.)	(The coil has no polarity.)	

Note: 1. An AC model has coil disconnection self-diagnosis.

2. For models with built-in diodes for coil surge absorption, check the coil polarity when wiring and wire all connections correctly.

3. The indicator is red for AC and green for DC.

4. The LED operation indicators indicate the energization of the coil and do not necessarily represent contact operation.







Note: 1. An AC model has coil disconnection self-diagnosis.

2. For models with built-in diodes for coil surge absorption, check the coil polarity when wiring and wire all connections correctly.

3. The indicator is red for AC and green for DC.

4. The LED operation indicators indicate the energization of the coil and do not necessarily represent contact operation.

Common Options (Order Separately)

Ordering Information

Front-mounting Sockets

Number of Pins	Applicable Relay Model	Terminal Type	Mounting Method	Appearance	Model	Hold-down Clips
		Screw terminal Finger protection structure * 1 (Screw size M3)	DIN Track or screw mounting		PYFZ-08-E	PYC-A1 *3
8	8 MY2□-GS-R	Screw terminal Finger protection structure * 1 (Screw size M3)	DIN Track or screw mounting		PYF08A-N	PYC-A1 *3
		Push-In Plus Terminal (Integrated Socket with release lever)	DIN Track or screw mounting *2		PYF-08-PU	
		Screw terminal Finger protection structure * 1 (Screw size M3)	DIN Track or screw mounting		PYFZ-14-E	PYC-A1 *3
14 MY4□-0	MY4⊡-GS-R	Screw terminal Finger protection structure * 1 (Screw size M3)	DIN Track or screw mounting	Carlo and	PYF14A-N	PYC-A1 *3
		Push-In Plus Terminal (Integrated Socket with release lever)	DIN Track or screw mounting *2		PYF-14-PU	

*1. In the finger protection type (PYFZ-□-E, and PYF□A-N), the terminal cover is integrated into the Socket. Round terminals cannot be used. Use forked terminals or ferrules instead.

*2. There are screw mounting holes in the DIN hooks on the PYF-D-PU. Pull out the DIN hook tabs to mount the Sockets with screws.

***3.** Model number of the applicable Mounting Bracket. Sold in sets of two.

Back-mounting Sockets

Number of Pins	Applicable Relay Model	Terminal Type	Appearance	Model	Hold-down Clips
8	MY2□-GS-R	PCB terminals		PY08-02	
14	MY4⊡-GS-R	PCB terminals		PY14-02	FIG-F #1

*1. If an MY IN Relay with a Latching Lever is used in combination with a PY -02 Socket for Relays with PCB Terminals and a PYC-P Mounting Bracket, the lever will not operate.

Socket accessories Mounting Bracket

Appearance *1	Model	Weight * 2	Application
	PYC-A1	Approx. 0.54 g	For joining the Socket and Relay
	РҮС-Р	Approx. 1.4 g	For joining the Socket and Relay

***1.** Describes the appearance when the Relay, Socket, and Mounting Bracket have been combined together.

***2.** The PYC-A1 includes two Mounting Brackets in one set. The weight specified above is the weight of one Mounting Bracket.

Ratings and Specifications

Characteristics

Sockets

							Dielectric strength				
Model	Conn ection	Number of Pins	Terminal Type	Ambient operating temperature	Ambient humidity	Continuous carry current	Between contact terminals of same polarity	Between contact terminals of different polarity	Between coil and contact terminals	Insulation resistance * 1	Weight
PYFZ-08-E			Screw	–55 to 70°C	5% to 85% RH	10 A	2,250 VAC 1 min	2,250 VAC 1 min	2,250 VAC 1 min	1,000 MΩ min. (500 VDC)	Approx. 32 g
PYF08A-N		8	terminal	–55 to 55°C	5% to 85% RH	7A * 3	2,000 VAC 1 min	2,000 VAC 1 min	2,000 VAC 1 min	1,000 MΩ min. (500 VDC)	Approx. 32 g
PYF-08-PU			Push-In Plus Terminal	−40 to 70°C	5% to 85% RH	10A * 2	2,000 VAC 1 min	2,000 VAC 1 min	2,000 VAC 1 min	1,000 MΩ min. (500 VDC)	Approx. 80 g
PYFZ-14-E	Front		Screw	–55 to 70°C	5% to 85% RH	6A	2,250 VAC 1 min	2,250 VAC 1 min	2,250 VAC 1 min	1,000 MΩ min. (500 VDC)	Approx. 50 g
PYF14A-N		14	terminal	–55 to 55°C	5% to 85% RH	5A *3	2,000 VAC 1 min	2,000 VAC 1 min	2,000 VAC 1 min	1,000 MΩ min. (500 VDC)	Approx. 50 g
PYF-14-PU		Push-In Plus Terminal	−40 to 70°C	5% to 85% RH	6A	2,000 VAC 1 min	2,000 VAC 1 min	2,000 VAC 1 min	1,000 MΩ min. (500 VDC)	Approx. 87 g	
PY08-02	Pook	8	PCB	–55 to 70°C	5% to 85% RH	7A	1,500 VAC 1 min	1,500 VAC 1 min	1,500 VAC 1 min	100 M Ω min.	Approx. 7.2 g
PY14-02	DACK	14	terminals	–55 to 70°C	5% to 85% RH	3A	1,500 VAC 1 min	1,500 VAC 1 min	1,500 VAC 1 min	100 MΩ min.	Approx. 10 g

***1.** For 500 VDC applied to the same location as for dielectric strength measurement.

*2. The continuous carry current of 10 A is for an ambient temperature of 55°C. At an ambient temperature of 70°C, the value is 7 A.
*3. When using the PYF08A-N or PYF14A-N at an ambient operating temperature exceeding 40°C, reduce the continuous carry current to 60%.

Socket Accessories For front-connecting Sockets Short Bars

Application	Applicable sockets	Model	Maximum carry current	Ambient operating temperature	Ambient operating humidity
		PYDN-7.75-020		−40 to 70°C	5% to 85%RH
For Contact terminals	PYF-08-PU(-L) PYF-14PU(-L)	PYDN-7.75-030	20 A		
(common)		PYDN-7.75-040			
		PYDN-7.75-200			
For Coil terminals	PYF-08-PU(-L) PYF-14PU(-L)	PYDN-31.0-080	20 A	−40 to 70°C	5% to 85%RH

Certified Standards Sockets

CSA certified (File No. LR031928)

Model	Ratings	Class number	Standard number
PYFZ-08-E	10A 250V		
PYFZ-14-E	6A 250V *		
PYF08A-N	7A 250V	2211.07	CSA C22 2 No14
PYF14A-N	7A 250V	321107	C3A C22.2 N014
PYF-08-PU	10A 250V		
PYF-14-PU	6A 250V *		

*When power is supplied to all four poles, use with a total power current that does not exceed 20 A.

UL Standards Certification (File No. E87929)

Model	Ratings	Standard number	Category	Listed/ Recognized
PYFZ-08-E	10A 250V			
PYFZ-14-E	6A 250V *			
PYF08A-N	7A 250V	111 508	SWIN/2	Pocognition
PYF14A-N	7A 250V	0L 308	300102	Recognition
PYF-08-PU	10A 250V			
PYF-14-PU	6A 250V *			

*When power is supplied to all four poles, use with a total power current that does not exceed 20 A.

TÜV Rheinland certification

Model	Ratings	Standard number	Certification No.	
PYFZ-08-E	10A 250V		R50405329	
PYFZ-14-E	6A 250V			
PYF08A-N	74.2501/	EN 61094	150004540	
PYF14A-N	7A 250V	EN 01904	J50224549	
PYF-08-PU	YF-08-PU 10A 250V *		DE0207E0E	
PYF-14-PU	6A 250V		R30327395	
	1		- F00 A1	

*Ratings are for an ambient temperature of up to 55°C. At an ambient temperature of 70°C, the value is 7A.

Dimensions

Connection Sockets

Front-mounting Sockets



PYF-08-PU

PYF-14-PU

MY-GS

Socket Accessories

Hold-down Clips PYC-A1 Set of 2 clips

PYC-P

Mounting Heights with Sockets (Unit: mm) Front-mounting Sockets

Back-mounting Sockets

Safety Precautions

Refer to the *Common Relay Precautions* for precautions that apply to all Relays in the website at the following URL: http://www.ia.omron.com/.

Precautions for Correct Use

Handling

For models with built-in diodes for coil surge absorption, check the coil polarity when wiring and wire all connections correctly.

Installation

There is no specifically required installation orientation, but make sure that the Relays are installed so that the contacts are not subjected to vibration or shock in their movement direction.

Using MY-GS Relays with Microloads with Infrequent Operation

If standard MYGS Relays are used to infrequently switch microloads, the contacts may become unstable and eventually result in poor contact. In this case, we recommend using the MY4Z-CBG Series, which has high contact reliability for microloads

Relay Replacement

To replace the Relay, turn OFF the power supply to the load and Relay coil sides to prevent unintended operation and possible electrical shock.

Applicable Sockets

- Use only combinations of OMRON Relays and Sockets.
- Use the following tightening torque for screws during wiring.

Model	Tightening torque
PYFZ-08-E	0.59 to 0.88 N⋅m
PYFZ-14-E	★ Use a No. 1 screwdriver.

• Use the following wire diameters as a guide for wiring. (Select the appropriate wire diameter for the current used.)

Model	Recommended wire diameter (mm ²)			
PYFZ-08-E	Stranded wire	0.75 to 2.5 mm ² AWG 18 to 14		
PYFZ-14-E	Solid wire	0.75 to 1.5 mm ² AWG 18 to 16		

Latching Levers

- Turn OFF the power supply when operating the latching lever.
- After you use the latching lever always return it to its original state. • Do not use the latching lever as a switch.
- The latching lever can be used for 100 operations min.

OMRON

OMRON AUTOMATION AMERICAS HEADQUARTERS • Chicago, IL USA • 847.843.7900 • 800.556.6766 • automation.omron.com

OMRON CANADA, INC. • HEAD OFFICE Toronto, ON, Canada • 416.286.6465 • 866.986.6766 • automation.omron.com

OMRON ELECTRONICS DE MEXICO • HEAD OFFICE Ciudad de México • 52.55.5901.4300 • 01.800.386.6766 • mela@omron.com

OMRON ELECTRONICS DE MEXICO • SALES OFFICE San Pedro Garza García, N.L. • 81.12.53.7392 • 01.800.386.6766 • mela@omron.com

OMRON ELECTRONICS DE MEXICO · SALES OFFICE Eugenio Garza Sada,León, Gto · 01.800.386.6766 · mela@omron.com

Authorized Distributor:

OMRON ELETRÔNICA DO BRASIL LTDA • HEAD OFFICE São Paulo, SP, Brasil • 55 11 5171-8920 • automation.omron.com

OMRON ARGENTINA • SALES OFFICE Buenos Aires, Argentina • +54.11.4521.8630 • +54.11.4523.8483 mela@omron.com

OTHER OMRON LATIN AMERICA SALES +54.11.4521.8630 • +54.11.4523.8483 • mela@omron.com

Controllers & I/O

Machine Automation Controllers (MAC)
 Motion Controllers

Programmable Logic Controllers (PLC)
 Temperature Controllers
 Remote I/O

Robotics

Industrial Robots
 Mobile Robots

Operator Interfaces

Human Machine Interface (HMI)

Motion & Drives

- Machine Automation Controllers (MAC)
 Motion Controllers
 Servo Systems
- Frequency Inverters

Vision, Measurement & Identification

Vision Sensors & Systems
 Measurement Sensors
 Auto Identification Systems

Sensing

- Photoelectric Sensors Fiber-Optic Sensors Proximity Sensors
- Rotary Encoders
 Ultrasonic Sensors

Safety

- Safety Light Curtains
 Safety Laser Scanners
 Programmable Safety Systems
- Safety Mats and Edges
 Safety Door Switches
 Emergency Stop Devices
- Safety Switches & Operator Controls Safety Monitoring/Force-guided Relays

Control Components

- Power Supplies Timers Counters Programmable Relays
- Digital Panel Meters
 Monitoring Products

Switches & Relays

- Limit Switches Pushbutton Switches Electromechanical Relays
- Solid State Relays

Software

Programming & Configuration • Runtime