

SPE PCB connector - SPE-T1-STRM-90-LED



1215778

<https://www.phoenixcontact.com/sk/products/1215778>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



SPE PCB connector, design: IEC 63171-2, degree of protection: IP20, number of positions: 2, 1 Gbps, CAT B (ISO/IEC 63171), connection method: THR solder connection, Single Pair Ethernet

Your advantages

- Connectors in accordance with IEC 63171-2
- THR solderable
- Robust industrial design
- THR solderable
- Data transmission up to 600 MHz

Commercial Data

Item number	1215778
Packing unit	100 pc
Minimum order quantity	100 pc
Note	Made to Order (non-returnable)
Sales Key	ABN
Product Key	ABNIBA
GTIN	4063151296742
Weight per Piece (including packing)	5.91 g
Weight per Piece (excluding packing)	5.91 g
Customs tariff number	85366990
Country of origin	DE

1215778

<https://www.phoenixcontact.com/sk/products/1215778>

Technical Data

Product properties

Type	SPE
Product type	Female insert
Number of positions	2
Pitch	7.62 mm
Number of slots	1
Locking type	Locking clip
Shielded	yes

Insulation characteristics

Overvoltage category	I
Degree of pollution	2

Electrical properties

Rated voltage (III/2)	72 V DC
Rated current	4 A
Frequency range	600 MHz
Insulation resistance	> 1 TΩ
Transmission medium	Copper

Connection data

Connection technology

Connection method	THR solder connection
-------------------	-----------------------

Dimensions

Width	7.52 mm
Height	13.33 mm
Length	20.6 mm
Pitch	7.62 mm

Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ni/Au
Contact carrier material	LCP

Cable / line

Test voltage Core/Core	1000 V DC
Test voltage Core/Shield	2250 V DC
Resistance to oil	yes
Flame resistance	UL 94 V0

1215778

<https://www.phoenixcontact.com/sk/products/1215778>

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 750
Insertion force per signal contact	< 1.50 N
Extraction force per signal contact	< 1.5 N

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Resistance to oil	yes

Standards and regulations

Flame resistance	UL 94 V0
Resistance to oil	yes

Mounting

Mounting type	PCB mounting
---------------	--------------

Processing notes

Moisture Sensitive Level	MSL1
--------------------------	------


SPE PCB connector - SPE-T1-STRM-90-LED



1215778

<https://www.phoenixcontact.com/sk/products/1215778>

Approvals

 cULus Recognized Approval ID: FILE E335024				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	60 V	1.4 A	-	-

SPE PCB connector - SPE-T1-STRM-90-LED



1215778

<https://www.phoenixcontact.com/sk/products/1215778>

Classifications

ECLASS

ECLASS-9.0	27440402
ECLASS-10.0.1	27440390
ECLASS-11.0	27440390

ETIM

ETIM 8.0	EC001121
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SPE PCB connector - SPE-T1-STRM-90-LED



1215778

<https://www.phoenixcontact.com/sk/products/1215778>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

SPE PCB connector - SPE-T1-STRM-90-LED



1215778

<https://www.phoenixcontact.com/sk/products/1215778>

Accessories

Patch cable

Patch cable - SPE-T1-CCP-SF/1,0/AWG22/CCP-SF - 1183807

<https://www.phoenixcontact.com/sk/products/1183807>



Patch cable, design: IEC 63171-2, degree of protection: IP20, cable length: 1 m, number of positions: 2, 1 Gbps, material: TPU, connection method: Crimp connection, connection cross section: AWG 22- 22, Single Pair Ethernet

Patch cable

Patch cable - SPE-T1-CCP-SF/2,0/AWG22/CCP-SF - 1183808

<https://www.phoenixcontact.com/sk/products/1183808>



Patch cable, design: IEC 63171-2, degree of protection: IP20, cable length: 2 m, number of positions: 2, 1 Gbps, material: TPU, connection method: Crimp connection, connection cross section: AWG 22- 22, Single Pair Ethernet

SPE PCB connector - SPE-T1-STRM-90-LED



1215778

<https://www.phoenixcontact.com/sk/products/1215778>

Patch cable

Patch cable - SPE-T1-CCP-SF/3,0/AWG22/CCP-SF - 1183810

<https://www.phoenixcontact.com/sk/products/1183810>



Patch cable, design: IEC 63171-2, degree of protection: IP20, cable length: 3 m, number of positions: 2, 1 Gbps, material: TPU, connection method: Crimp connection, connection cross section: AWG 22- 22, Single Pair Ethernet

Patch cable

Patch cable - SPE-T1-CCP-SF/5,0/AWG22/CCP-SF - 1183811

<https://www.phoenixcontact.com/sk/products/1183811>



Patch cable, design: IEC 63171-2, degree of protection: IP20, cable length: 5 m, number of positions: 2, 1 Gbps, material: TPU, connection method: Crimp connection, connection cross section: AWG 22- 22, Single Pair Ethernet

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT s.r.o.

Námestie Mateja Korvína 1

811 07 Bratislava

+421 2 3210 1470

obchod.sk@phoenixcontact.com