


Item no.: 721-110/037-000
 Product description: FEMALE CONNECTOR WITH LOCKING LEVER 10 POLE PIN SPACING 5 MM / 0.197 IN 100% PROTECTED AGAINST MISMATING WITH CODING FINGERS WITH 2 LATCHES



Produkt kann von Bild abweichen / product may differ

Packing unit 25 pieces

RoHS compliant

Product group	3 (Multi Conn. System)
Weight	19.69 g
Color	light gray
No. of connection Points	10
No. of potentials	10
pole count	10
Height	14.3 mm
Height	0.563 in
Width	66.6 mm
Width	2.622 in
Depth	29.6 mm
Depth	1.165 in
Pin spacing from	5 mm
Pin spacing from	0.197 in
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	4 kV
Current intensity EN	16 A

Pollution degree	2
Measured voltage EN	630 V
Measured shock voltage	4 kV
Current intensity EN	16 A



Connection method	CAGE CLAMP® CONNECTION
Cross section [mm ²]	0.08 - 2.5 mm ²
Wiring method	solid
Cross section [mm ²]	0.08 - 2.5 mm ²
Cross section [mm ²]	0.25 - 1.5 mm ²
Cross section [mm ²]	0.25 - 2.5 mm ²
Cross section [AWG]	28 - 12 AWG
Strip length from	8 mm
Strip length to	9 mm
Material group	I
xxx-xxx/035-000	Strain relief plate 50 mm
xxx-xxx/xxx-045	1-PE-3
xxx-xxx/xxx-047	1-2-3-4-5-...



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
721-110/037-000	ABS	04-HG469925/1-PDA	250	16	0,08-2,5
721-110/037-000	BV	11914/AO	250	16	
721-110/037-000	CCA	5764	250	16	0,08-2,5
721-110/037-000	CSA	154112-1466354	300	15	28-12
721-110/037-000	DNV	E-9218	250	16	0,08-2,5
721-110/037-000	GL	17296-00HH	250	16	
721-110/037-000	KEMA	2083746.02	250	16	0,08-2,5
721-110/037-000	KR	HMB05880-EL003	250/400	12/16	2,5
721-110/037-000	LR	96/20035	250	16	0,08-2,5
721-110/037-000	RMR	11130002	250	16	0,08-2,5
721-110/037-000	UR	E45171	600	15	28-12
721-110/037-000	UR	E45172	300	15	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected