



Single-deck terminal block - Modular version - Pitch 15mm - 1÷2 poles

GENERAL INFORMATION

pitch:	15 mm
housing height:	16,80 mm
housing depth:	8.9 mm
dimensional class:	medium
wire section:	2.5 mm ² / 14 AWG
clamp opening size:	2.8 × 2.7 mm
wire stripping:	max 7 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	16A
voltage:	750V
test voltage:	3 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

APPROVALS DATA



EN 60998-1

current:	16A
voltage:	750V
wire section:	2.5mm ²
torque:	0.5Nm
FILE:	EP149



EN 60998-1

current:	16A
voltage:	750V
wire section:	2.5mm ²
torque:	0.5Nm
FILE:	40023956



UL 1059

current:	16A factory / 15A field
voltage:	300V
wire section:	14÷30AWG
torque:	4.5Lb-in
FILE:	E178356

MATERIALS

housing:	PA - UL 94 V0
----------	---------------

AVAILABLE COLOURS

screw:
clamp/spring:
terminal:

Galvanized steel
Nickel-coated copper alloy
Tin-plated copper alloy



other colours:

upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
1	MVE271-15-V	N/A	N/A	N/A
2	MVE272-15-V	N/A	N/A	N/A
..	MVE27..-15-V	N/A	N/A	N/A