



## Single-deck terminal block - Modular version - Pitch 5mm - 2÷12 poles

### GENERAL INFORMATION

pitch:	5 mm
housing height:	11,50 mm
housing depth:	7.5 mm
dimensional class:	slow
wire section:	2.5 mm <sup>2</sup> / 14 AWG
clamp opening size:	2.6 × 2.4max mm
wire stripping:	max 6.5 mm
operating temperature:	-40°C ÷ +130°C

### ELECTRICAL CHARACTERISTICS

current:	24A
voltage:	450V
test voltage:	2.5 kVrms/60s

### MECHANICAL CHARACTERISTICS

screw:	M2.5
max. torque:	0.4 Nm / 3.6 in.lbs

### APPROVALS DATA



current:	-	-	UL 1059
voltage:	-	-	20A factory / 15A field
wire section:	-	-	300V
torque:	-	-	14÷30AWG
FILE:	-	-	3.6Lb-in
			E178356

### MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel
clamp/spring:	Tin-plated copper alloy

### AVAILABLE COLOURS



other colours: upon request

terminal:

Tin-plated copper alloy

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MVE112-5-V	N/A	N/A	N/A
3	MVE113-5-V	N/A	N/A	N/A
4	MVE114-5-V	N/A	N/A	N/A
5	MVE115-5-V	N/A	N/A	N/A
6	MVE116-5-V	N/A	N/A	N/A
7	MVE117-5-V	N/A	N/A	N/A
8	MVE118-5-V	N/A	N/A	N/A
9	MVE119-5-V	N/A	N/A	N/A
10	MVE1110-5-V	N/A	N/A	N/A
11	MVE1111-5-V	N/A	N/A	N/A
12	MVE1112-5-V	N/A	N/A	N/A