



## Male plug-in connector - Horizontal dual row - Modular - Pitch 3,81mm - 02 ÷ 03 poles

### GENERAL INFORMATION

pitch:	3,81 mm
housing height:	22,65 mm
housing depth:	22.5 mm
dimensional class:	medium
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-40°C ÷ +130°C

### ELECTRICAL CHARACTERISTICS

current:	11A
voltage:	160V
impulse voltage:	2.5 kV

### MECHANICAL CHARACTERISTICS

### APPROVALS DATA



-  
-

current:



EN 61984  
8A 2/3 poles



UL 1059  
11A factory / 11A field

voltage:	-	6A 4÷12 poles	160V	300V
FILE:	-	40048261	E178356	

### MATERIALS

housing: PA - UL 94 V0  
 screw: n/a  
 clamp/spring: n/a  
 terminal: Tin-plated copper alloy

### AVAILABLE COLOURS

(STD) **GN** **GY** **BK** **BL** **RD** **YL** **OG**

other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	PDV02-3,81-H-M	N/A	N/A	N/A
03	PDV03-3,81-H-M	N/A	N/A	N/A