

M12 A-cod 4-pol an/- f/- PPI PUR 5.0m



Image is for illustration purposes only. Please refer to product description.

Part number	97 00 000 0669
Specification	M12 A-cod 4-pol an/- f/- PPI PUR 5.0m
HARTING eCatalogue	https://harting.com/97000000669

Identification

Category	System cabling
Series	Circular connectors M12
Element	Cable assemblies
Specification	Pre-assembled on one side
Connector 1	M12 A-coding Female Angled Overmoulded PushPull (outer)
Type of cable	Copper cable (round)
Description of the cable	Halogen-free

Version

Cable length	5 m
Number of cores	4
Core structure	4x 0.34 mm ²
Termination method	Crimp termination
Shielding	Unshielded
Number of contacts	4
Coding	A-coding

Technical characteristics

Rated current	4 A
Rated voltage	250 V



Pushing Performance
Since 1945

Technical characteristics

Limiting temperature	-25 ... +80 °C moved -40 ... +80 °C unmoved
Degree of protection acc. to IEC 60529	IP65 / IP67 mated condition
Cable diameter	4.2 mm
Minimum bending radius	10x Cable diameter (repeated bending) 5x Cable diameter (singular bending)

Material properties

Material (cable)	PUR (polyurethane)
Colour (cable)	RAL 7021 (black grey)
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

Specifications and approvals

Approvals	CE
-----------	----

Commercial data

Packaging size	1
Country of origin	Germany
European customs tariff number	85444290
eCl@ss	27060311 Assembled sensor actuator-line
ETIM	EC001855
UNSPSC 24.0	26121604