

KMK 1 - Plastic cable markers

0830745

<https://www.phoenixcontact.com/sk/products/0830745>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Plastic cable markers, transparent, unlabeled, mounting type: Assembly with cable ties, cable diameter: ≥ 6 mm, lettering field size: 25 x 6 mm



Your advantages

- Plastic cable markers for insert labels, for assembly with cable binders
- Plastic cable markers for marking and bundling conductors and cables indoors
- The markers have eyelets and are attached with cable binders
- The marked insert label is protected from dirt by the sealing cap

Commercial data

Item number	0830745
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	BG2
Product key	BG231A
Catalog page	Page 234 (C-3-2019)
GTIN	4046356738583
Weight per piece (including packing)	0.955 g
Weight per piece (excluding packing)	0.955 g
Customs tariff number	39269097
Country of origin	PL

KMK 1 - Plastic cable markers



0830745

<https://www.phoenixcontact.com/sk/products/0830745>

Technical data

Product properties

Product type	Marker carrier cable
Type	Mounting set

Dimensions

Width	6 mm
Height	6 mm
Length	25 mm

External dimensions

Outside diameter	6 mm ... 50 mm
------------------	----------------

Material specifications

Color	transparent
Material	Polyethylene
Components	free from silicone and halogen

Cable/line

External cable diameter	≥ 6 mm
-------------------------	--------

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Temperature resistance

Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 80 °C (105 °C)	Test passed
Specification	ISO 175:2010 (following)
Test duration	168 h
Diesel [CAS No. 68476-34-6]	Test passed
IRM 901	Test passed
IRM 902	Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed

KMK 1 - Plastic cable markers



0830745

<https://www.phoenixcontact.com/sk/products/0830745>

Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %
Shelf life	2 years

Mounting

Mounting type	Assembly with cable ties
---------------	--------------------------

KMK 1 - Plastic cable markers



0830745

<https://www.phoenixcontact.com/sk/products/0830745>

Classifications

ECLASS

ECLASS-11.0	27281105
ECLASS-12.0	27281105
ECLASS-13.0	27281105

ETIM

ETIM 9.0	EC001530
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

KMK 1 - Plastic cable markers

0830745

<https://www.phoenixcontact.com/sk/products/0830745>

Accessories

UCT-EMP (25X6) - Snap-in markers

1014117

<https://www.phoenixcontact.com/sk/products/1014117>



Snap-in markers, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, lettering field size: 25 x 6 mm, Number of individual labels: 15

US-EMP (25X6) - Snap-in markers

0829435

<https://www.phoenixcontact.com/sk/products/0829435>



Snap-in markers, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, lettering field size: 26 x 6.1 mm, Number of individual labels: 88

KMK 1 - Plastic cable markers

0830745

<https://www.phoenixcontact.com/sk/products/0830745>

US-EMP (25X6)-1 - Snap-in markers

0802754

<https://www.phoenixcontact.com/sk/products/0802754>



Snap-in markers, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, lettering field size: 25 x 6 mm, Number of individual labels: 84

EMT (25X6)R - Insert label

0817264

<https://www.phoenixcontact.com/sk/products/0817264>



Insert label, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: insert, cable diameter range: 10 ... 25 mm, lettering field size: 25 x 6 mm, Number of individual labels: 5000

KMK 1 - Plastic cable markers

0830745

<https://www.phoenixcontact.com/sk/products/0830745>



MM-EMT (EX6)R C1 WH/BK - Insert label

0803963

<https://www.phoenixcontact.com/sk/products/0803963>



Insert label, Roll, white/black, unlabeled, can be labeled with: THERMOFOX, THERMOMARK GO, THERMOMARK GO.K, mounting type: snapped, lettering field size: continuous x 4 mm, Number of individual labels: 1

ESL (25X6) - Insert strip

0801849

<https://www.phoenixcontact.com/sk/products/0801849>



Insert strip, Sheet, white, unlabeled, can be labeled with: Office printing systems, CMS-P1-PLOTTER, mounting type: insert, lettering field size: 25 x 6 mm, Number of individual labels: 252

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT s.r.o.

Námestie Mateja Korvína 1

811 07 Bratislava

+421 2 3210 1470

obchod.sk@phoenixcontact.com