

https://www.phoenixcontact.com/sk/products/1837243



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Cable housing, product range: KGG-PC 4



#### Commercial data

Item number	1837243
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	ААН
Product key	AAHZDF
Catalog page	Page 522 (C-1-2013)
GTIN	4017918111281
Weight per piece (including packing)	19.1 g
Weight per piece (excluding packing)	18.6 g
Customs tariff number	39269097
Country of origin	PL



https://www.phoenixcontact.com/sk/products/1837243



### Technical data

#### Product properties

Product type	Cable housing			
Product family	KGG-PC 4			
Number of positions	5			
Pitch	0 mm			
Data management status				
Article revision	03			
Material specifications				
Flammability rating according to UL 94	НВ			
Dimensions				
Pitch	0 mm			



https://www.phoenixcontact.com/sk/products/1837243



### Classifications

UNSPSC 21.0

#### **ECLASS**

	ECLASS-11.0	27460402		
	ECLASS-12.0	27460402		
	ECLASS-13.0	27460402		
ETIM				
	ETIM 9.0	EC002943		
UN	ISPSC			

39121400



https://www.phoenixcontact.com/sk/products/1837243



### Environmental product compliance

EU R	oHS
------	-----

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



https://www.phoenixcontact.com/sk/products/1837243




#### Accessories

#### KGS-MSTB 2,5/ DST - Cable housing

1784914

https://www.phoenixcontact.com/sk/products/1784914



Transparent label carrier, can be marked with marker strips SBS 2.5/7.5

#### PC 4/5-ST-7,62 - PCB connector

1804933

https://www.phoenixcontact.com/sk/products/1804933



PCB connector, nominal cross section: 4 mm², color: green, nominal current: 20 A, rated voltage (III/2): 630 V, contact surface: Sn, contact connection type: Socket, number of potentials: 5, number of rows: 1, number of positions: 5, number of connections: 5, product range: PC 4/..-ST, pitch: 7.62 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - Locking clip, plug-in system: COMBICON PC 4, locking: without, mounting: without, type of packaging: packed in cardboard

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT s.r.o. Námestie Mateja Korvína 1 811 07 Bratislava +421 2 3210 1470 obchod.sk@phoenixcontact.com