



Recommand PCB Layout

**MATERIAL**

Contact Pin : Brass  
 Insulator: NYLON 66 UL94V-0

**SPECIFICATION**

Voltage Rating : 250V AC/DC  
 Current Rate : 3A AC/DC  
 Dielectric voltage : 800V AC for one minute  
 Insulation Resistance : 1000MΩMin  
 Contact Resistance : 20mΩMax  
 Operation Temperature : -25°C to +85°C

755-71-xx T W 0 6  
 1 2 3 4 5

1. 7: Green Product  
 9: Green Product High Temp.
2. No. of contacts per row
3. G: Gold flash  
 S: Selective  
 T: Tin plated
4. S: Crystal insulator  
 W: White insulator
5. Pinrex internal code.

POLES	Dimensions(mm)	
	A	B
2	2.50	7.50
3	5.00	10.00
4	7.50	12.50
5	10.00	15.00
6	12.50	17.50
7	15.00	20.00
8	17.50	22.50
9	20.00	25.00
10	22.50	27.50
11	25.00	30.00
12	27.50	32.50
13	30.00	35.00
14	32.50	37.50
15	35.00	40.00



		TOLERANCE		UNITS : mm		OLD PART NO.		TITLE	
		.0 =±.30		SCALE NONE		DRAWER 胡雨婷		2.5mm WIRE TO BOARD	
B 增加尺寸3.60		.00 =±.20		SIZE A4		CHECK 李劍		CONNECTOR, STRAIGHT TYPE	
A RELEASE		.000 =±.XXX		SHEET 1 OF 1		APP'D 李劍		NEW PART NO. 755-71-xxTW06	
REV. DESCRIPTION		.0000=±.		REV. B		DRAW NO. 755-71-xxTW06(B版)		PINREX TECHNOLOGY CORP.	
		ANG.=±3'						频锐科技股份有限公司	
								PINREX TECHNOLOGY CORP.	