

## InduCom 9p 1T-entry hexscrew M3



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                     |
|--------------------|-------------------------------------------------------------------------------------|
| Part number        | 61 03 001 1010 160                                                                  |
| Specification      | InduCom 9p 1T-entry hexscrew M3                                                     |
| HARTING eCatalogue | <a href="https://harting.com/61030011010160">https://harting.com/61030011010160</a> |

### Identification

|                             |                     |
|-----------------------------|---------------------|
| Category                    | Hoods / Housings    |
| Series                      | D-Sub               |
| Identification              | InduCom             |
| Type of hood/housing        | Shell housing       |
| Description of hood/housing | With internal earth |

### Version

|                         |                                                                                                                           |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Size                    | D-Sub 1                                                                                                                   |
| Number of cable entries | 1                                                                                                                         |
| Cable entry             | 1x                                                                                                                        |
| Strain relief           | An additional InduCom cable clamp or a crimp flange - ferrule combination is available dependant on the use of the cable. |
| Locking type            | Hexagonal screw with captive washer Thread M3                                                                             |
| ground connection       | With internal grounding block                                                                                             |
| 2 parts                 | Yes                                                                                                                       |
| Separable               | Yes                                                                                                                       |

### Technical characteristics

|                                        |                          |
|----------------------------------------|--------------------------|
| Tightening torque                      | 0.4 Nm ground connection |
|                                        | 0.4 Nm cover screw       |
|                                        | 0.4 Nm Locking screw     |
| Limiting temperature                   | -55 ... +125 °C          |
| Degree of protection acc. to IEC 60529 | IP30                     |



**Pushing Performance**  
Since 1945

## Material properties

|                                      |                      |
|--------------------------------------|----------------------|
| Material (hood/housing)              | Zinc die-cast        |
| Material (screw)                     | Steel, nickel plated |
| Length                               | 38.6 mm              |
| Width                                | 31 mm                |
| Height                               | 14.8 mm              |
| RoHS                                 | compliant            |
| ELV status                           | compliant            |
| China RoHS                           | e                    |
| REACH Annex XVII substances          | Not contained        |
| REACH ANNEX XIV substances           | Not contained        |
| REACH SVHC substances                | Not contained        |
| California Proposition 65 substances | Not contained        |

## Commercial data

|                                |                     |
|--------------------------------|---------------------|
| Packaging size                 | 10                  |
| Net weight                     | 39.1 g              |
| Country of origin              | China               |
| European customs tariff number | 85389099            |
| GTIN                           | 5713140222526       |
| eCl@ss                         | 27440213 D-Sub hood |
| ETIM                           | EC001133            |
| UNSPSC 24.0                    | 39121416            |