


Data sheet Product LAM 7 K 100 12



Cooling aggregates>Miniature cooling aggregates

70 x 70 mm, with axial fan, integrated clamp

- compact design
- homogeneous heat distribution
- mounting possible on any side
- powerful axial-fan motor
- other lengths, special designs and machinings according to customer's specifications
- other surfaces, fan types and fan voltages upon request

Features

width:	70 mm
height:	70 mm
length:	100 mm
thermal resistance:	0.67 - 0.15 K/W
surface:	natural colour anodised

Technical Drawing



Fan

type:	ADDA AD0712UB-A7BGP
dimensions:	70x70x25 mm
tension:	12 V DC
power inout:	5 W
max. air volume:	82 m ³ /h
temperature range:	-10°C... +70°C
noise level:	47.4 dB(A)

speed:	5,000 min⁻¹
weight:	90 g
failure rate (L ₁₀):	70.000 h (40°C)
type:	ADDA AD0724UB-A7BGP
dimensions:	70x70x25 mm
tension:	24 V DC
power inout:	6.2 W
max. air volume:	82 m³/h
temperature range:	-10°C... +70°C
noise level:	47.4 dB(A)
speed:	5,000 min⁻¹
weight:	90 g
failure rate (L ₁₀):	70.000 h (40°C)