

ÖLFLEX® SERVO FD 781 CY

Screened, low capacitive servo cable with PVC outer sheath for flexible power chain application

ÖLFLEX® SERVO FD 781 CY - Low capacitive and screened servo motor cables for mean load in power chain applications.

Info

Core Line Performance - Medium to increased travel lengths or acceleration

EMC-compliant



Interference signals



Power chain



Oil-resistant

Benefits

Well-proven and reliable

Longer cable connection possible between frequency converter and motor due to low capacitance design

Copper screening complies with EMC requirements and protects against electromagnetic interference

Application range

Connecting cable between Frequency converter and motor

In power chains or moving machine parts

For power circuits in machine cabling

In dry, damp or wet interiors with normal mechanical stress conditions

Only for outdoor use within the indicated operating temperature range, with UV-protection

Product features

Oil-resistant

Flame retardant acc. to IEC 60332-1-2

Last Update (11.11.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® SERVO FD 781 CY

Low-adhesive surface

Norm references / Approvals

Based on VDE 0250 / 0285

For use in power chains: Please comply with assembly guideline Appendix T3

Product Make-up

Extra-fine wire strand made of bare copper wires (class 6)

Core insulation: polypropylene (PP)

Cores twisted in short lay lengths

Non-woven wrapping

Tinned-copper braiding

PVC outer sheath, orange (RAL 2003)

Technical Data

| | |
|--|---|
| Classification ETIM 5: | ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable |
| Classification ETIM 6: | ETIM 6.0 Class-ID: EC000104 ETIM 6.0 Class-Description: Control cable |
| Core identification code: | Black with white numbers acc. to VDE 0293-1 |
| Conductor stranding: | Extra-fine wire according to VDE 0295, class 6/IEC 60228 class 6 |
| Minimum bending radius: | Flexing: up from 7.5 x outer diameter Fixed installation: 4 x outer diameter |
| Nominal voltage: | U0/U: 600/1000 V |
| Test voltage: | Core/Core: 4 kV Core/Screen: 4 kV |
| Protective conductor: | G = with gn-ye protective conductor |
| Temperature range: | Flexing: -5°C to +70°C Fixed installation: -40°C to +80°C |
| Bending cycles & operation parameters: | See Selection Table A2-1 in the appendix of our online catalogue |

Note

Unless specified otherwise, the shown product values are nominal values at room temperature. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

ÖLFLEX® SERVO FD 781 CY

| Article number | Number of cores and mm ² per conductor | Outer diameter [mm] | Copper index (kg/km) | Weight (kg/km) |
|-------------------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® SERVO FD 781 CY | | | | |
| 0036320 | 4 G 1.5 | 9.8 | 89 | 157 |
| 0036321 | 4 G 2.5 | 11.9 | 133.8 | 233 |
| 0036322 | 4 G 4.0 | 13.5 | 210.9 | 335 |
| 0036324 | 4 G 10.0 | 19.7 | 488.2 | 747 |
| 0036325 | 4 G 16.0 | 23.9 | 744.8 | 1109 |
| 0036327 | 4 G 35.0 | 33.3 | 1,565.4 | 2264 |
| 0036328 | 4 G 50.0 | 38.3 | 2,174.9 | 3090 |

Last Update (11.11.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.deYou can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03_16