

CRC EP FOOD GREASE

Synthetic

Ref. : 32457



1. GENERAL DESCRIPTION

EP grease for the lubrication of equipment submitted to extreme heavy operation circumstances (high loads, temperatures, dust,...) .Provides long-term lubrication on all food processing equipment where incidental food contact may occur. Protects against corrosion in wet or saturated environments.

2. FEATURES

- Corresponds to the most severe demands in the industry.
- Extends the lifetime of the equipment and prevents contamination problems as regulated by the HACCP.
- Excellent mechanical stability.
- Remarkable resistance to high loads.
- High resistance against water.
- Very good anti oxidation and anti corrosion characteristics.
- NSF registration : H1 (registration number : 139907)

3. APPLICATIONS

- Designed to cover a wide range of food processing safe applications, encompassing :
 - wet and saturated environments,
 - heavily loaded applications,
 - where there is a presence of dust and other contaminants.
 -
- Especially recommended for lubrication of granule presses in the fodder and sugar industry.

4. DIRECTIONS


CRC EP Food Grease can be applied by hand, or by using a standard grease gun.

Never mix with other lubricants.



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com





CRC EP FOOD GREASE

Synthetic

Ref. : 32457

A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.

Based upon the present state of our knowledge and information received from our suppliers, evaluation of this product indicates that it is free from nut oils and their derivatives.

5. TYPICAL PRODUCT DATA

Aspect	: white
Thickener	: aluminium complex
Base Oil	: synthetic
Base oil viscosity	: 160 mm ² /s @ 40°C
Worked penetration	: 255 – 295 mm ⁻¹
Standard operating temperature	: -40 to +180 °C
Water resistance (DIN 51 807T1)	: 1 - 90
Copper corrosion	: 1a
EP additive	: yes
4-ball load failure test	: typical 4000 N
4-ball wear	: 0,45 mm
dN value	: 400000
designation (DIN 51502)	: KHC2R-40
NSF classification	: H1

6. PACKAGING

Cartridge : 12 x 400 g

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 32457 03 0514 04
Date : 28 September 2017



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

