

## Han-Eco Mod.6-HCC-M32-glanded-reinf.lev.



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                               |
|--------------------|-------------------------------------------------------------------------------|
| Part number        | 19 41 106 6722                                                                |
| Specification      | Han-Eco Mod.6-HCC-M32-glanded-reinf.lev.                                      |
| HARTING eCatalogue | <a href="https://harting.com/19411066722">https://harting.com/19411066722</a> |

### Identification

|                             |                                                          |
|-----------------------------|----------------------------------------------------------|
| Category                    | Hoods / Housings                                         |
| Series of hoods/housings    | Han-Eco® Modular                                         |
| Type of hood/housing        | Cable to cable housing                                   |
| Description of hood/housing | With integrated cable gland<br>Reinforced locking levers |

### Version

|                         |                                            |
|-------------------------|--------------------------------------------|
| Size                    | 6 B                                        |
| Module slots            | 3                                          |
| Version                 | Top entry                                  |
| Number of cable entries | 1                                          |
| Cable entry             | 1x M32                                     |
| Locking type            | Double locking lever                       |
| Field of application    | Hoods/housings for industrial applications |

### Technical characteristics

|                                        |                                                |
|----------------------------------------|------------------------------------------------|
| Limiting temperature                   | -40 ... +125 °C                                |
| Note on the limiting temperature       | For use as a connector according to IEC 61984. |
| Number of relockings                   | ≥500                                           |
| Degree of protection acc. to IEC 60529 | IP65                                           |
| Clamping range                         | 13 ... 21 mm                                   |



**Pushing Performance**  
Since 1945

## Material properties

|                                                            |                                          |
|------------------------------------------------------------|------------------------------------------|
| Material (hood/housing)                                    | Polyamide (PA)<br>Fibre-glass reinforced |
| Colour (hood/housing)                                      | RAL 9005 (jet black)                     |
| Material (seal)                                            | NBR                                      |
| Colour (seal)                                              | RAL 9005 (jet black)                     |
| Material (locking)                                         | Polyamide (PA)<br>Fibre-glass reinforced |
| Colour (locking)                                           | RAL 9005 (jet black)                     |
| Material flammability class acc. to UL 94                  | V-0                                      |
| Material flammability class acc. to UL 94 (locking levers) | V-0                                      |

## Specifications and approvals

|                |                                                             |
|----------------|-------------------------------------------------------------|
| Specifications | IEC 61984<br>EN 45545-2 Fire protection on railway vehicles |
| UL / CSA       | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076  |
| Approvals      | CE                                                          |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 156.9 g                                  |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140829848                            |
| eCl@ss                         | 27440202 Shell for industrial connectors |
| ETIM                           | EC000437                                 |
| UNSPSC 24.0                    | 39121466                                 |