



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司



Winstar Display Co., LTD

華凌光電股份有限公司



WEB: <http://www.winstar.com.tw> E-mail: sales@winstar.com.tw

SPECIFICATION

MODULE NO.: WF104FTIAMLNNO#

General Specifications

Item	Dimension	Unit
Size	10.4	inch
Dot Matrix	1024 x R.G.B. x 768	dots
Module dimension	236.0*176.9*5.7	mm
Active area	211.2 *158.4	mm
Dot pitch	0.20625 x 0.20625	mm
LCD type	TFT, Normally White, Transmissive	
Gray scale inversion direction	6 o'clock	
Backlight Type	LED, Normally White	
Interface	LVDS	
Touch Panel	Without Touch Panel	
Surface	Anti-Glare	

*Color tone slight changed by temperature and driving voltage.

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	°C
Storage Temperature	TST	-30	—	+80	°C

Electrical Characteristics

Item	Symbol	Min	Typ	Max	Units
LCD Drive Voltage (Logic)	VDD	3.0	3.3	3.6	V
VDD Current	Black Pattern IDD	-	TBD	(0.25)	A
VDD Power Consumption	Black Pattern PDD	-	-	(0.84)	W
Rush Current	Irush	-	-	1.5	A
Allowable Logic/LCD Drive Ripple Voltage	VDDrp	-	-	(200)	mV

Interface


Signal Connector Type


Item	Description
Type/Part Number	MSB24013P20HA (Manufacture by STM)
Mating Receptacle / Type (Reference)	P24013P20 or compatible

Signal Connector Pin Assignment

Pin No.	Symbol	Description
1	VDD	Power Supply, 3.3V (typical)
2	VDD	Power Supply, 3.3V (typical)
3	VSS	Ground
4	REV	Reverse Scan selection {High:2.5(min), 3.3(typ),3.6(max); Low: 0.5(max)}
5	Rin1-	-LVDS differential data input (R0-R5,G0)
6	Rin1+	+LVDS differential data input (R0-R5,G0)
7	VSS	Ground
8	Rin2-	-LVDS differential data input (G1-G5,B0-B1)
9	Rin2+	+LVDS differential data input (G1-G5,B0-B1)
10	VSS	Ground
11	Rin3-	-LVDS differential data input (B2-B5,HS,VS,DE)
12	Rin3+	+LVDS differential data input (B2-B5,HS,VS,DE)
13	VSS	Ground
14	ClkIN-	-LVDS differential clock input
15	ClkIN+	+LVDS differential clock input
16	GND	Ground
17	Rin4-	-LVDS differential data input (R6-R7,G6-G7,B6-B7)
18	Rin4+	+VDS differential data input (R6-R7,G6-G7,B6-B7)
19	SEL68	6/8 bits LVDS data input selection(H:8bits L/NC:6bits)
20	Bist	Internal use

Contour Drawing





The non-specified tolerance of dimension is ± 0.3 mm .