

## Data sheet

280-837

### 4-CONDUCTOR EARTH TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE



## Technical data

Package size 100 pieces.

Cross section from [mm <sup>2</sup> ]	0.08 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	2.5 mm <sup>2</sup>
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Weight	12.827 g
Color	green-yellow
Wiring type	Front-entry
No. of connection Points	4
No. of potentials	1
Height	28 mm
Height	1.1 in
Width	5 mm
Width	0.197 in
Depth	75 mm
Depth	2.95 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in

---

**Data sheet**

280-837

**4-CONDUCTOR EARTH TERMINAL BLOCK CENTRE MARKING  
FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE**

---

Approval	Voltage	Current	Approval number	Notes
BV	800	20	07436/C0	
CCA			NL4912	
CSA			154112-1536071	
Dep.MaE	600	25	CS4865N	
DNV	800	20	E6999	
GL			17295-00HH	
KEMA			98.2759.03	
LR	800	20	91/20112(E1)	
RMR	800	20	99.00007.250	
RosTesT	800	20	B09523	
UL			E45172	

## Data sheet

280-837

### 4-CONDUCTOR EARTH TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

Accessories	Item number
ADJACENT JUMPER NOMINAL CURRENT 24 A	280-402
ADJACENT JUMPER NOMINAL CURRENT 24 A	280-422
ALTERNATE JUMPER NOMINAL CURRENT 24 A	280-409
ALUMINIUM CARRIER RAIL 35 X 7.5 MM, 1.5 MM / 0.059 IN THICK	210-196
CARRIER FOR SPARE ADJACENT JUMPERS SUITABLE FOR ADJACENT JUMPER SERIES 279-284, BANANENSTECKER SERIES 215	209-100
COMB TYPE JUMPER BAR INSULATED	280-482
COMB TYPE JUMPER BAR INSULATED	280-483
COMB TYPE JUMPER BAR INSULATED	280-484
COMB TYPE JUMPER BAR INSULATED	280-485
COMB TYPE JUMPER BAR INSULATED	280-490
COPPER CARRIER RAIL 35 X 15 MM, 2.3 MM / 0.091 IN THICK	210-198
COVER CARRIER TYPE 1	709-167
COVER PLATE 1 MM / 0.039 IN THICK	284-336
COVER PLATE 1 MM / 0.039 IN THICK	284-346
COVER TYPE 1	709-153
END AND INTERMEDIATE PLATE 2.5MM / 0.098 IN THICK	280-314
END AND INTERMEDIATE PLATE 2.5MM / 0.098 IN THICK	280-315
END MODULE MODULAR	249-142
GROUP MARKER CARRIER FOR UP TO 1 WMB-MARKER OR 2 MARKER TAGS	209-142
GROUP MARKER CARRIER FOR UP TO 2 WMB-MARKER OR 5 MARKER TAGS	209-141
GROUP MARKER CARRIER FOR UP TO 3 WMB-MARKER OR 8 MARKER TAGS	209-140
HOLD BLOCK FOR ISOLATED MOUNTING ON DIN 35 RAIL	209-106
Individual wire jumpers	individual jumper
INSULATION STOP 0.08 - 0.2 MM <sup>2</sup>	280-470
INSULATION STOP 0.25 - 0.5 MM <sup>2</sup>	280-471
INSULATION STOP 0.75 - 1 MM <sup>2</sup>	280-472
MODULAR TEST PLUG ADAPTER MODULE WIDTH 5 MM / 0.197 IN	280-418
Open individual wire jumpers ends	individual jumper open end
OPERATING STICKER FOR FRONT-ENTRY RAIL-MOUNTED TERMINAL BLOCKS	210-186
OPERATING TOOL FITTED FOR SERIES 264, 280, 281	209-130
OPERATING TOOL INSULATED	280-432
OPERATING TOOL INSULATED	280-433
OPERATING TOOL INSULATED	280-434
OPERATING TOOL INSULATED	280-435
OPERATING TOOL INSULATED	280-436
OPERATING TOOL INSULATED	280-437
OPERATING TOOL INSULATED	280-438

## Data sheet

280-837

### 4-CONDUCTOR EARTH TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

---

OPERATING TOOL INSULATED	280-439
OPERATING TOOL INSULATED	280-440
PIVOTABLE GROUP MARKER CARRIER	249-105
PROTECTIVE WARNING MARKER WITH HIGH VOLTAGE SYMBOL, BLACK	280-415
PUSH-IN TYPE WIRE JUMPERS L = 180 MM / 7.087 IN	249-123
PUSH-IN TYPE WIRE JUMPERS WIRE LENGTH 110 MM / 4.331 IN	249-126
PUSH-IN TYPE WIRE JUMPERS WIRE LENGTH 250 MM / 9.843 IN	249-127
PUSH-IN TYPE WIRE JUMPERS WIRE LENGTH 60 MM / 2.362 IN	249-125
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019 IN	210-257
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019 IN	210-258
SCREWDRIVER Type 2, bar (3,5 x 0,5) mm	210-120
SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 2, bar (3,5 x 0,5) mm	210-620
SCREWLESS END STOP 10 MM / 0.394 IN WIDE	249-117
SCREWLESS END STOP 6 MM / 0.236 IN WIDE	249-116
SEPARATOR PLATE 2MM 0.079 IN THICK	280-334
SEPARATOR PLATE 2MM 0.079 IN THICK	280-335
SPACER MODULE MODULAR	249-107
SPACER MODULE MODULAR	249-143
SPACER MODULE MODULE WIDTH 5 MM / 0.197 IN	280-419
SPARE FIXING / RETAINING SCREWS	209-196
SPARE KNURLED NUT	210-549
STAGGERED JUMPER FROM 1 TO 2	780-452
STAGGERED JUMPER FROM 1 TO 3	780-453
STAGGERED JUMPER FROM 1 TO 4	780-454
STAGGERED JUMPER FROM 1 TO 5	780-455
STAGGERED JUMPER FROM 1 TO 6	780-456
STAGGERED JUMPER FROM 1 TO 7	780-457
STAGGERED JUMPER FROM 1 TO 8	780-458
STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK	210-114
STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK	210-197
STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK	210-506
STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK	210-508
STEEL CARRIER RAIL 35 X 15 MM, 2.3 MM / 0.091 IN THICK	210-118
STEEL CARRIER RAIL 35 X 15 MM, 2.3 MM / 0.091 IN THICK	210-548
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-112
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-113
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-162
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-229
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-504
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-505
SYRINGE CONTENT: 20 ml ALU-PLUS CONTACT PASTE	249-130

---

---

**Data sheet****280-837****4-CONDUCTOR EARTH TERMINAL BLOCK CENTRE MARKING  
FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE**

---

TEST PLUG 6 MM / 0.236 IN WIDE	281-407
TEST PLUG ADAPTER 5 MM / 0.197 IN WIDE	280-404
TEST PLUG ADAPTER MODULE MODULAR	249-106
TEST PLUG ADAPTER MODULE MODULAR	249-141
TEST PLUG FOR TEST PLUG 4 MM / 0.157 IN Ø	209-170
WFB CONTINUOUS MARKING STRIPS FOR SELF-MARKING	210-612
WIRE COMMONING CHAIN INSULATED	210-103
WIRE COMMONING CHAIN INSULATED	210-123
WIRE COMMONING CHAIN INSULATED	709-110
WIRE COMMONING CHAIN INSULATED	709-111
WIRE COMMONING CHAIN INSULATED	709-112
WMB MULTI MARKING SYSTEM PLAIN	793-501
WMB MULTI MARKING SYSTEM PLAIN	793-5501
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-006
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-005
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-002
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-007
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-012
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-017
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-023
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-024