



## Male plug-in connector - Horizontal - Dual row - Pitch 5mm - 07/10/12/19 poles

### GENERAL INFORMATION

pitch:	5 mm
housing height:	28,60 mm
housing depth:	22.3 mm
dimensional class:	medium
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-40°C ÷ +130°C

### ELECTRICAL CHARACTERISTICS

current:	10A
voltage:	250V
impulse voltage:	4 kV

### MECHANICAL CHARACTERISTICS

### APPROVALS DATA



EN 61984

current:	12A
voltage:	250V
FILE:	CA02.04178



EN 61984

current:	12A
voltage:	250V
FILE:	40005779



UL 1059

current:	12A factory / 12A field
voltage:	300V
FILE:	E178356

## MATERIALS

housing: PA - UL 94 V0  
screw: n/a  
clamp/spring: n/a  
terminal: Tin-plated copper alloy

## AVAILABLE COLOURS



other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
07	PDH07-5	N/A	N/A	N/A
10	PDH10-5	N/A	N/A	N/A
12	PDH12-5	N/A	N/A	N/A
19	PDH19-5	N/A	N/A	N/A