

Data sheet Product SL 11 SMD 052 32 Z SM



PCB connectors>Male headers

□ 0.635 mm

... packing (option) - additions:

SL 11 SMD 040-104 ... SM; ... B SM: 6-40 contacts

SL 11 SMD 040-062 ... B TR: 26-40 contacts, 250 pcs/reel

SL 11 SMD 040-078 ... B TR: 6-24 contacts, **250 pcs/reel**

SL 11 SMD 104-130 ... B TR: 6-24 **contacts**, 150 pcs/reel

Features

pitch:	2.54 x 2.54 mm
--------	----------------

no. of contacts:	32
------------------	----

contact material:	CuSn-alloy
-------------------	------------

surface of contact:	tin-plated
---------------------	------------

surface contact / contact sleeve:	• Ni+≥0.2µm Au • Ni+4...6µm Sn
--------------------------------------	---

version:	male header
----------	-------------

volume resistance:	≤5 mΩ
--------------------	-------

nominal current:	3 A
------------------	-----

nominal voltage:	250 V AC
------------------	----------

test voltage:	2000 V
---------------	--------

insulating body material:	PA 4.6. GF
---------------------------	------------

temperature range:	• -40°C... +163°C • (260°C/10 s)
--------------------	---

class of inflammability:	UL 94 V-0
--------------------------	-----------

specific insulation resistance:	>10 ⁷ Ω·m
------------------------------------	----------------------

connection type:	SMD
------------------	-----

reflow solderable:	yes
--------------------	-----

bar magazine

Figure 1 consists of three technical drawings of test specimens, labeled (a), (b), and (c). Each drawing shows a side view of a specimen with a base and several vertical pins. Drawing (a) shows a specimen with a base width of 2,8 mm and a pin diameter of 0,635 mm. The spacing between the pins is labeled as $n/2 \times 2,54$. Drawing (b) shows a specimen with a base width of 8,5 mm and a pin diameter of 0,635 mm. The spacing between the pins is labeled as 2,54 mm. Drawing (c) shows a specimen with a base width of 8,5 mm and a pin diameter of 0,635 mm. The spacing between the pins is labeled as 2,54 mm. The drawings also indicate the position of Pin 1 and the height of the pins.

S: 4.0 mm

[illegible]