



## Male plug-in connector - Horizontal - Modular version - Pitch 7,62mm - 02÷08 poles

### GENERAL INFORMATION

pitch:	7,62 mm
housing height:	18,85 mm
housing depth:	7.7 mm
dimensional class:	medium
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-40°C ÷ +105°C

### ELECTRICAL CHARACTERISTICS

current:	16A
voltage:	500V
impulse voltage:	6 kV

### MECHANICAL CHARACTERISTICS

### APPROVALS DATA



current:	-	-	-
voltage:	-	-	-
FILE:	-	-	-

UL 1059  
22A factory / 20A field  
300V  
E178356

### MATERIALS

### AVAILABLE COLOURS

housing: PA - UL 94 V0  
 screw: n/a  
 clamp/spring: n/a  
 terminal: Tin-plated copper alloy



other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	PF02-7,62-H-M	N/A	N/A	N/A
03	PF03-7,62-H-M	N/A	N/A	N/A
04	PF04-7,62-H-M	N/A	N/A	N/A
05	PF05-7,62-H-M	N/A	N/A	N/A
06	PF06-7,62-H-M	N/A	N/A	N/A
07	PF07-7,62-H-M	N/A	N/A	N/A
08	PF08-7,62-H-M	N/A	N/A	N/A