



## Single-deck terminal block - Modular version - Pitch 10mm - 1÷6 poles

### GENERAL INFORMATION

pitch:	10 mm
housing height:	13,50 mm
housing depth:	8.3 mm
dimensional class:	slow
wire section:	1.5 mm <sup>2</sup> / 16 AWG
clamp opening size:	2.6 × 1.8 mm
wire stripping:	max 7 mm
operating temperature:	-40°C ÷ +130°C

### ELECTRICAL CHARACTERISTICS

current:	17.5A
voltage:	750V
test voltage:	3 kVrms/60s

### MECHANICAL CHARACTERISTICS

screw:	M2.5
max. torque:	0.4 Nm / 3.6 in.lbs

### APPROVALS DATA



EN 60998-1



EN 60998-1



UL 1059

current: 17.5A

17.5A

17.5A factory / 10A field

voltage: 750V

750V

600V

wire section: 1.5mm<sup>2</sup>

1.5mm<sup>2</sup>

16÷30AWG

torque: 0.4Nm

0.4Nm

3.6Lb-in

FILE: EP151

40019705

E178356

### MATERIALS

### AVAILABLE COLOURS

housing: PA - UL 94 V0  
 screw: Galvanized steel  
 clamp/spring: Tin-plated copper alloy  
 terminal: Tin-plated copper alloy



other colours:

upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
1	MVE151-10-V	N/A	N/A	N/A
2	MVE152-10-V	N/A	N/A	N/A
3	MVE153-10-V	N/A	N/A	N/A
4	MVE154-10-V	N/A	N/A	N/A
5	MVE155-10-V	N/A	N/A	N/A
6	MVE156-10-V	N/A	N/A	N/A
..	MVE15..-10-V	N/A	N/A	N/A