


U.I. Lapp GmbH	<b>PRODUCT INFORMATION</b>	
	<b>SKINDICHT® SVRE-M</b>	14.11.2013

With incised sealing ring for adjustment to several cable diameters  
Fewer sizes need to be kept in stock



Robust



Reliability



### Application range

Brass cable gland with hexagonal fitting and variable incised sealing ring.

### Design

Metric connection thread acc. to EN 50262

### Note

Refer to SKINDICHT® EV for additional accessories  
Counter nut to be used: SKINDICHT® SM-M

### Remark

Viton® is a registered trademark of DuPont de Nemours  
Photographs are not to scale and do not represent detailed images of the respective products.

### Technical Data


Caution:	The installation dimensions can be found in appendix T21
On request:	Available with long connection thread Available with VITON® incised ring
Material:	Body: nickel-plated brass Incised seal: CR/NBR
Protection rating:	IP 54
Temperature range:	-20°C to +80°C


Product Management	Document: LAPP_PRO1006EN.pdf	1 / 3
--------------------	------------------------------	-------

**SKINDICHT® SVRE-M**

14.11.2013

Part number	Article designation / size	Incised sealing ring ØF (mm)	Max. internal Ø (mm)	Function thread PG	SW1/SW2 mm	Overall length/ C (mm)	Thread length/ D (mm)	Pieces / PU
SKINDICHT® SVRE-M								
52104980	16 x 1,5	5/8	12	9	18 / 15	21,6	5.0	100
52104990	20 x 1,5	7/10/12.5	15	11	22 / 18	22,6	6.0	50
52105000	20 x 1,5	7/10.5/13/16	15	13.5	22 / 20	25,6	6.0	50
52105010	20 x 1,5	8/10.5/13.5/16	15	16	24 / 22	26,6	6.0	50
52105002	25 x 1,5	11/15/18/20	20	21	30 / 28	29,6	7.0	50
52105003	32 x 1,5	19/23/27/31	27	29	40 / 37	32,6	8.0	50
52105004	40 x 1,5	25/28/31/35	34	36	50 / 47	37,6	8.0	20
52105005	50 x 1,5	35.5/39/42.5/46	44	42	57 / 54	42,6	9.0	5
52105006	63 x 1,5	40.5/44/47/50.5	54	48	66 / 60	45,1	10.0	5

U.I. Lapp GmbH	<b>PRODUCT INFORMATION</b>	
	<b>SKINDICHT® SVRE-M</b>	14.11.2013



Product Management	Document: LAPP_PRO1006EN.pdf	3 / 3
--------------------	------------------------------	-------